



STIGA

# 2022 Product range

## MOWING

---

### **78 Robot mowers**

### **80 Lawn mowers**

- 80 Battery
- 86 Petrol
- 92 Corded
- 93 Push cylinder

### **94 Axial mowers**

### **95 Front mowers**

- 98 Decks

### **99 Zero turn**

### **100 Tractors**

- 100 Battery
- 102 Petrol

## CLEANING

---

### **108 Blowers and Vacuum shredder**

- 108 Battery
- 110 Petrol
- 111 Corded

### **112 High pressure cleaners**

### **113 Sweepers**

- 113 Petrol
- 114 Push

### **115 Snow throwers**

- 115 Battery
- 116 Petrol

## CUTTING AND TRIMMING

---

### **118 Brushcutters and lawn trimmers**

- 118 Battery
- 120 Petrol
- 125 Corded

### **126 Hedge trimmers and pole trimmers**

- 126 Battery
- 128 Petrol
- 129 Corded

### **130 Multi-tools**

- 130 Battery
- 131 Petrol

### **132 Multi-mate**

### **133 Pole saws, pruners and chainsaws**

- 133 Battery
- 134 Petrol
- 137 Corded

## SOIL AND GROUND CARE

---

### **138 Chipper and shredders**

### **139 Scarifiers**

- 139 Petrol
- 139 Corded

### **140 Tillers**

### **141 Scythe**

## ACCESSORIES

---

### **142 Batteries and chargers**

### **144 Accessories**

### **166 Safety clothing**

### **168 Lubricants and oil**

### **170 Toys**



## MOWING

# Robot mowers with AGS technology



### Stig-A

	5000	3000	1500
Level	Expert	Expert	Experience
POWER			
Battery capacity	2 X 5 Ah	5 Ah	5 Ah
Maximum working time	270 min	150 min	150 min
Battery kit	Included	Included	Included
Motor type	Brushless	Brushless	Brushless
Maximum working area	5000 m <sup>2</sup>	3000 m <sup>2</sup>	1500 m <sup>2</sup>
CUTTING SYSTEM			
Cutting method	Organized	Organized	Organized
Cutting width	26 cm	26 cm	18 cm
Cutting height range	20 - 65 mm	20 - 65 mm	20 - 60 mm
Cutting height adjustment	Electronic	Electronic	Electronic
Cutting height on a zone	Yes	Yes	No
Smart cutting height adjustment	Yes	Yes	Upgradable
Blade type	6 Pivoting blades	6 Pivoting blades	4 Pivoting blades
Blade speed	2400 rpm	2400 rpm	2850 rpm
Rain sensors	Yes	Yes	Yes
Maximum slope	50%	50%	45%
NAVIGATION AND DEVICES			
APP Control	4G	4G	4G
Virtual zone exclusion	Yes	Yes	Yes
Grass care organized cut	Yes	Yes	Yes
Back to charge	Automatic short path	Automatic short path	Automatic short path
STANDARD EQUIPMENT AND INSTALLATION			
Reference GPS antenna	Included	Included	Included
Docking station	Yes	Yes	Yes
Base protection cover	-	-	Optional
PRODUCT SAFETY			
Obstacle detection sensors	Yes	Yes	Yes
Obstacle notification	Yes	Yes	Upgradable
Lift sensor	Yes	Yes	Yes
Theft alert	Yes	Yes	Yes
Art. N.	2R9106028/ST1	2R9102028/ST1	2R7102028/ST1

The technology of the robot is based on data communication between the STIGA Cloud and the robot itself. The subscription fee is mandatory for Stig-A to work and depends on the amount of data required.

# Robot mowers



Stig	1200	600	300
Level	Essential	Essential	Essential
POWER			
Battery capacity	5 Ah	2.5 Ah	2 Ah
Maximum working time	150 min	90 min	60 min
Battery kit	Included	Included	Included
Motor type	Brushless	Brushless	Brushless
Maximum working area	1200 m <sup>2</sup>	600 m <sup>2</sup>	300 m <sup>2</sup>
CUTTING SYSTEM			
Cutting method	Random	Random	Random
Go-to-Cut points	5	3	1
Cutting width	18 cm	18 cm	18 cm
Cutting height range	20 - 60 mm	20 - 60 mm	20 - 60 mm
Blade type	4 Pivoting blades	4 Pivoting blades	4 Pivoting blades
Blade speed	2850 rpm	2850 rpm	2850 rpm
Eco-mode	Yes	No	No
Rain sensors	Yes	Yes	No
Maximum slope	45%	45%	45%
NAVIGATION AND DEVICES			
APP Control	Bluetooth	Bluetooth	Bluetooth
User interface	Keypad	Keypad	Keypad
Back to charge	On wire / Run Beside Wire (RBW)	On wire / Run Beside Wire (RBW)	On wire
STANDARD EQUIPMENT AND INSTALLATION			
Installation wire length	Not included	Not included	100 m
Fixing nails	7	7	200
Connectors	2	2	4
Docking station	Yes	Yes	Yes
Base protection cover	Optional	Optional	Optional
PRODUCT SAFETY			
Obstacle detection sensors	Yes	Yes	Yes
Lift sensor	Yes	Yes	Yes
Theft alert	Yes	Yes	Yes
Art. N.	2R3102018/ST2	2R3101018/ST2	2R3101118/ST1

# Battery lawn mowers



## Multiclip

	950e V	747e V	547e S Kit	547e Kit
Level	Expert	Experience	Experience	Experience
Series	9	7	5	5
POWER				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery capacity	2 x 4 Ah	2 x 4 Ah	2 x 4 Ah	4 Ah
Battery kit	Not included	Not included	Included	Included
DRIVING				
Driving	Self-propelled	Self-propelled	Self-propelled	Push
Wheels	210/210 mm grooved aluminum wheels on ball bearings	180/180 mm grooved wheels on ball bearings with soft tread	180/180 mm grooved wheels on ball bearings with soft tread	180/180 mm grooved wheels on ball bearings with soft tread
MOWING				
Cutting width	48 cm	45 cm	45 cm	45 cm
Cutting method	Mulching	Mulching	Mulching	Mulching
Maximum working area	1300 m <sup>2</sup>	800 m <sup>2</sup>	800 m <sup>2</sup>	500 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized	Centralized	Centralized
Cutting height positions	5 positions	5 positions	5 positions	5 positions
Cutting height range	31 - 75 mm	31 - 80 mm	31 - 80 mm	31 - 80 mm
COMFORT				
Deck material	Galvanized steel	Galvanized steel	Steel	Steel
Handlebar type	Fulcrum + keypad and soft grip	Fulcrum + keypad and soft grip	Fulcrum + soft grip	Fulcrum + soft grip
Adjustable handlebar	Yes	Yes	Yes	Yes
Foldable handlebar	Yes	Yes	Yes	Yes
Front handle	Yes	Yes	Yes	Yes
Product weight	TBC	TBC	22 kg	22 kg
Art. N.	291503098/ST2	298473278/ST2	298472058/ST1	298471058/ST2



## Twinclip

	950e VR	950e V
Level	Expert	Expert
Series	9	9
POWER		
Power source	Lithium-ion battery	Lithium-ion battery
Battery capacity	2 x 7.5 Ah	2 x 7.5 Ah
Battery kit	Not included	Not included
DRIVING		
Driving	Self-propelled	Self-propelled
Wheels	200/ROLLER grooved wheels on ball bearings	210/240 mm grooved aluminum wheels on ball bearings
MOWING		
Cutting width	48 cm	48 cm
Cutting method	Collecting	Collecting, Mulching, Side discharge, Rear discharge
Maximum working area	950 m²	1100 m²
Cutting height adjustment	Centralized	Centralized
Cutting height positions	8 positions	7 positions
Cutting height range	13 - 65 mm	25 - 77 mm
Collector type	Textile	Textile (plug-in) with warn
Collector capacity	80 L	70 L
Deck material	Galvanized steel	Galvanized steel
COMFORT		
Handlebar type	Ergonomic 25 mm adj. by button with keypad + soft grip	Ergonomic 25 mm adj. by button with keypad + soft grip
Adjustable handlebar	Yes	Yes
Foldable handlebar	Yes	Yes
Front handle	Yes	Yes
Product weight	41 kg	42 kg
Art. N.	294519098/ST1	294513898/ST2

# Battery lawn mowers



## Combi

	955e V	950e V	753e V	748e V
Level	Expert	Expert	Experience	Experience
Series	9	9	7	7
POWER				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery capacity	2 x 7.5 Ah	2 x 7.5 Ah	2 x 5 Ah	2 x 4 Ah
Battery kit	Not included	Not included	Not included	Not included
DRIVING				
Driving	Self-propelled	Self-propelled	Self-propelled	Self-propelled
Wheels	200/280mm grooved wheels on ball bearings with soft tread	180/240 mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread
MOWING				
Cutting width	53 cm	48 cm	51 cm	46 cm
Cutting method	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge
Maximum working area	1000 m <sup>2</sup>	950 m <sup>2</sup>	600 m <sup>2</sup>	550 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized	Centralized	Centralized
Cutting height positions	5 positions	5 positions	6 positions	6 positions
Cutting height range	25 - 80 mm	25 - 65 mm	22 - 80 mm	22 - 80 mm
Collector type	Hybrid with warn	Hybrid with warn	Hybrid with warn	Hybrid with warn
Collector capacity	70 L	70 L	60 L	60 L
Deck material	Galvanized steel	Galvanized steel	Galvanized steel	Galvanized steel
COMFORT				
Handlebar type	Fulcrum + keypad and soft grip	Fulcrum + keypad and soft grip	Fulcrum + keypad and soft grip	Fulcrum + keypad and soft grip
Adjustable handlebar	Yes	Yes	Yes	Yes
Foldable handlebar	Yes	Yes	Yes	Yes
Front handle	Yes	Yes	Yes	Yes
Product weight	36 kg	33 kg	31 kg	29 kg
Art. N.	294557898/ST2	294507898/ST2	2L0537878/ST2	2L0487878/ST2



344e Kit	340e Kit	336e Kit
<b>Essential</b>	<b>Essential</b>	<b>Essential</b>
<b>3</b>	<b>3</b>	<b>3</b>
Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
5 Ah	4 Ah	2 Ah
Included	Included	Included
Push	Push	Push
150/250 mm grooved wheels	150/250 mm grooved wheels	140/170 mm grooved wheels
42 cm	38 cm	34 cm
Collecting, Mulching, Rear discharge	Collecting, Mulching, Rear discharge	Collecting, Mulching, Rear discharge
400 m²	350 m²	200 m²
Centralized	Centralized	Centralized
6 positions	6 positions	6 positions
25 - 75 mm	25 - 75 mm	25 - 75 mm
Textile	Textile	Textile
50 L	40 L	35 L
Polypropylene / ABS	Polypropylene / ABS	Polypropylene / ABS
Flat with cam locks and comfort switch + soft grip	Flat with cam locks and comfort switch + soft grip	Flat with cam locks and comfort switch + soft grip
Yes	Yes	Yes
Yes	Yes	Yes
Yes	Yes	Yes
15 kg	14 kg	12 kg
294426068/ST2	294386068/ST2	294346068/ST2



# Battery lawn mowers



Collector	548e S Kit	548e Kit	543e Kit	140e Kit
Level	Experience	Experience	Experience	Essential
Series	5	5	5	1
POWER				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery capacity	2 x 4 Ah	4 Ah	4 Ah	2 x 4 Ah
Battery kit	Included	Included	Included	Included
DRIVING				
Driving	Self-propelled	Push	Push	Push
Wheels	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/200mm grooved wheels on ball bearings with soft tread	140/170 mm grooved wheels
MOWING				
Cutting width	46 cm	46 cm	41 cm	38 cm
Cutting method	Collecting, Rear discharge	Collecting, Rear discharge	Collecting, Rear discharge	Collecting
Maximum working area	550 m <sup>2</sup>	400 m <sup>2</sup>	400 m <sup>2</sup>	350 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized	Centralized	Centralized
Cutting height positions	6 positions	6 positions	6 positions	6 positions
Cutting height range	22 - 80 mm	22 - 80 mm	22 - 65 mm	25 - 75 mm
Collector type	Hybrid with warn	Hybrid with warn	Hybrid with warn	Hybrid
Collector capacity	60 L	60 L	60 L	40 L
Deck material	Steel	Steel	Steel	Polypropylene
COMFORT				
Handlebar type	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip	Ergonomic with double hand switch and cam locks + soft grip
Adjustable handlebar	Yes	Yes	Yes	Yes
Foldable handlebar	Yes	Yes	Yes	Yes
Front handle	Yes	Yes	Yes	Yes
Product weight	29 kg	24 kg	23 kg	12.26 kg
Art. N.	2L0486008/ST1	2L0485008/ST1	2L0431008/ST2	291382068/ST2



136e Kit	132e Kit
<b>Essential</b>	<b>Essential</b>
<b>1</b>	<b>1</b>
Lithium-ion battery	Lithium-ion battery
2 x 2 Ah	4 Ah
Included	Included
Push	Push
140/170 mm grooved wheels	140/140 mm grooved wheels
34 cm	30 cm
Collecting	Collecting
250 m²	150 m²
Centralized	On axles
6 positions	3 positions
25 - 75 mm	30 - 70 mm
Hybrid	Plastic
35 L	30 L
Polypropylene	Polypropylene
Ergonomic with double hand switch and cam locks + soft grip	Flat with single hand switch
Yes	Yes
Yes	Yes
Yes	Yes
11.75 kg	8.79 kg
291342068/ST2	291302068/ST2



## Aero

	132e Kit
Level	<b>Essential</b>
Series	<b>1</b>
<b>POWER</b>	
Power source	Lithium-ion battery
Battery capacity	2 x 4 Ah
Battery kit	Included
<b>DRIVING</b>	
Driving	Push
Wheels	-
<b>MOWING</b>	
Cutting width	30 cm
Cutting method	TBD
Maximum working area	TBD
Cutting height adjustment	No
Cutting height positions	No
Cutting height range	No
Deck material	Polypropylene
<b>COMFORT</b>	
Handlebar type	Ergonomic with double hand switch and cam locks + soft grip
Foldable handlebar	No
Front handle	No
Product weight	8.79 kg
Art. N.	298302068/ST1

# Petrol lawn mowers



## Multiclip

	950 V	950 VE	750 S	747 SD
Level	Expert	Expert	Experience	Experience
Series	9	9	7	7
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Engine Brand	Honda	STIGA	STIGA	STIGA
Engine model	GCVx170 OHV Autochoke	ST 200 LS OHV Autochoke Powered by STIGA	ST 170 OHV Autochoke Powered by STIGA	ST 140 OHV Autochoke Powered by STIGA
Displacement	167 cc	196 cc	166 cc	139 cc
Engine rotation speed	2900 rpm	2900 rpm	2900 rpm	2900 rpm
Fuel tank capacity	0.95 L	0.90 L	1 L	0.75 L
Engine Oil tank capacity	0.40 L	0.50 L	0.55 L	0.50 L
DRIVING				
Driving	Self-propelled	Self-propelled	Self-propelled	Self-propelled
Wheels	210/210 mm grooved aluminum wheels on ball bearings	210/210mm grooved wheels on ball bearings with soft tread	210/210mm grooved wheels on ball bearings with soft tread	180/180 mm grooved wheels on ball bearings with soft tread
MOWING				
Cutting width	48 cm	48 cm	48 cm	45 cm
Cutting method	Mulching	Mulching	Mulching	Mulching, Side discharge
Maximum working area	1700 m <sup>2</sup>	1700 m <sup>2</sup>	1700 m <sup>2</sup>	1500 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized	Centralized	Centralized
Cutting height positions	5 positions	5 positions	5 positions	5 positions
Cutting height range	31 - 75 mm	31 - 75 mm	31 - 75 mm	31 - 80 mm
COMFORT				
Deck material	Galvanized steel	Galvanized steel	Galvanized steel	Galvanized steel
Handlebar type	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip
Adjustable handlebar	Yes	Yes	Yes	No
Foldable handlebar	Yes	Yes	Yes	Yes
Front handle	Yes	Yes	Yes	Yes
Starter	Recoil	Electric start by button	Recoil	Recoil
Product weight	37 kg	35 kg	34 kg	27 kg
Art. N.	291503038/ST1	291503548/ST1	291502048/ST2	298472848/ST2



550	547 S	547 D	547
<b>Experience</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
<b>5</b>	<b>5</b>	<b>5</b>	<b>5</b>
Petrol	Petrol	Petrol	Petrol
STIGA	STIGA	STIGA	STIGA
ST 140 OHV Autochoke Powered by STIGA	ST 120 OHV Autochoke Powered by STIGA	ST 120 OHV Autochoke Powered by STIGA	ST 120 OHV Autochoke Powered by STIGA
139 cc	123 cc	123 cc	123 cc
2900 rpm	2900 rpm	2900 rpm	2900 rpm
0.75 L	0.75 L	0.75 L	0.75 L
0.50 L	0.50 L	0.50 L	0.50 L
Push	Self-propelled	Push	Push
210/210mm grooved wheels on ball bearings with soft tread	180/180 mm grooved wheels on ball bearings with soft tread	180/180 mm grooved wheels on ball bearings with soft tread	180/180 mm grooved wheels on ball bearings with soft tread
48 cm	45 cm	45 cm	45 cm
Mulching	Mulching	Mulching, Side discharge	Mulching
1700 m²	1500 m²	1500 m²	1500 m²
4 levers	3 levers	4 levers	4 levers
5 positions	5 positions	5 positions	5 positions
31 - 75 mm	31 - 80 mm	31 - 80 mm	31 - 80 mm
Steel	Steel	Steel	Steel
Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip
Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes
Yes	No	No	No
Recoil	Recoil	Recoil	Recoil
28 kg	25 kg	25 kg	23 kg
291501048/ST2	298472048/ST2	298471848/ST2	298471048/ST2



# Petrol lawn mowers



## Twinclip

	955 B	955 VE	950 VE	950 V
Level	Expert	Expert	Expert	Expert
Series	9	9	9	9
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Engine Brand	Honda	Honda	STIGA	STIGA
Engine model	GXV 160 OHV	GCVx170 OHV Autochoke	ST 200 LS OHV Autochoke Powered by STIGA	ST 200 OHV Autochoke Powered by STIGA
Displacement	163 cc	167 cc	196 cc	196 cc
Engine rotation speed	2800 rpm	2900 rpm	2900 rpm	2900 rpm
Fuel tank capacity	1.80 L	0.95 L	0.90 L	1 L
Engine Oil tank capacity	0.65 L	0.40 L	0.50 L	0.50 L
DRIVING				
Driving	Self-propelled	Self-propelled	Self-propelled	Self-propelled
Wheels	210/240 mm grooved aluminum wheels on ball bearings	210/240mm grooved wheels on ball bearings	210/240mm grooved wheels on ball bearings	210/240mm grooved wheels on ball bearings
MOWING				
Cutting width	53 cm	53 cm	48 cm	48 cm
Cutting method	Collecting, Mulching, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge
Maximum working area	2500 m²	2500 m²	2000 m²	2000 m²
Cutting height adjustment	Centralized	Centralized	Centralized	Centralized
Cutting height positions	7 positions	7 positions	7 positions	7 positions
Cutting height range	25 - 77 mm	25 - 77 mm	25 - 77 mm	25 - 77 mm
Collector type	Textile (plug-in) with warn	Textile (plug-in) with warn	Textile (plug-in) with warn	Textile (plug-in) with warn
Collector capacity	70 L	70 L	70 L	70 L
Deck material	Galvanized steel	Galvanized steel	Galvanized steel	Galvanized steel
COMFORT				
Handlebar type	Ergonomic 25 mm adj. by button + soft grip	Ergonomic 25 mm adj. by button + soft grip	Ergonomic 25 mm adj. by button + soft grip	Ergonomic 25 mm adj. by button + soft grip
Adjustable handlebar	Yes	Yes	Yes	Yes
Foldable handlebar	Yes	Yes	Yes	Yes
Front handle	Yes	Yes	Yes	Yes
Starter	Recoil	Electric start by button	Electric start by button	Recoil
Product weight	55 kg	47 kg	44 kg	43 kg
Art. N.	294568038/ST2	294563538/ST2	294513548/ST1	294513048/ST1

# Petrol lawn mowers



Collector	548 S	543
Level	Experience	Experience
Series	5	5
POWER		
Power source	Petrol	Petrol
Engine Brand	STIGA	STIGA
Engine model	ST 120 OHV Autochoke Powered by STIGA	ST 120 OHV Autochoke Powered by STIGA
Displacement	123 cc	123 cc
Engine rotation speed	2900 rpm	2900 rpm
Fuel tank capacity	0.75 L	0.75 L
Engine Oil tank capacity	0.50 L	0.50 L
DRIVING		
Driving	Self-propelled	Push
Wheels	200/200mm grooved wheels on ball bearings with soft tread	200/200mm grooved wheels on ball bearings with soft tread
MOWING		
Cutting width	46 cm	41 cm
Cutting method	Collecting, Rear discharge	Collecting, Rear discharge
Maximum working area	1200 m <sup>2</sup>	1000 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized
Cutting height positions	6 positions	6 positions
Cutting height range	22 - 65 mm	22 - 65 mm
Collector type	Hybrid with warn	Hybrid with warn
Collector capacity	60 L	60 L
Deck material	Steel	Steel
COMFORT		
Handlebar type	Fulcrum + soft grip	Fulcrum + soft grip
Adjustable handlebar	Yes	Yes
Foldable handlebar	Yes	Yes
Front handle	Yes	Yes
Starter	Recoil	Recoil
Product weight	28 kg	25 kg
Art. N.	2L0482048/ST2	2L0431048/ST2

# Petrol lawn mowers



## Combi

	955 VE	955 V H	955 V	753 V
Level	Expert	Expert	Expert	Experience
Series	9	9	9	7
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Engine Brand	STIGA	Honda	STIGA	Honda
Engine model	ST 200 LS OHV Autochoke Powered by STIGA	GCVx200 OHV Autochoke	ST 200 OHV Autochoke Powered by STIGA	GCVx170 OHV Autochoke
Displacement	196 cc	201 cc	196 cc	167 cc
Engine rotation speed	2900 rpm	2900 rpm	2900 rpm	2900 rpm
Fuel tank capacity	0.90 L	0.95 L	1 L	0.95 L
Engine Oil tank capacity	0.50 L	0.40 L	0.50 L	0.40 L
DRIVING				
Driving	Self-propelled	Self-propelled	Self-propelled	Self-propelled
Wheels	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread
MOWING				
Cutting width	53 cm	53 cm	53 cm	51 cm
Cutting method	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge
Maximum working area	2000 m <sup>2</sup>	2000 m <sup>2</sup>	2000 m <sup>2</sup>	1800 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized	Centralized	Centralized
Cutting height positions	5 positions	5 positions	5 positions	6 positions
Cutting height range	25 - 80 mm	25 - 80 mm	25 - 80 mm	22 - 80 mm
Collector type	Hybrid with warn	Hybrid with warn	Hybrid with warn	Hybrid with warn
Collector capacity	70 L	70 L	70 L	60 L
Deck material	Galvanized steel	Galvanized steel	Galvanized steel	Galvanized steel
COMFORT				
Handlebar type	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip
Adjustable handlebar	Yes	Yes	Yes	Yes
Foldable handlebar	Yes	Yes	Yes	Yes
Front handle	Yes	Yes	Yes	Yes
Starter	Electric start by button	Recoil	Recoil	Recoil
Product weight	40 kg	TBC	38 kg	35 kg
Art. N.	294557548/ST1	294557838/ST3	294557848/ST2	2L0537838/ST2



753 SE	753 S	748 V	748 SE	748 S
<b>Experience</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
<b>7</b>	<b>7</b>	<b>7</b>	<b>7</b>	<b>7</b>
Petrol	Petrol	Petrol	Petrol	Petrol
STIGA	STIGA	Honda	STIGA	STIGA
ST 170 LS OHV Autochoke Powered by STIGA	ST 170 OHV Autochoke Powered by STIGA	GCVx145 OHV Autochoke	ST 140 LS OHV Autochoke Powered by STIGA	ST 140 OHV Autochoke Powered by STIGA
166 cc	166 cc	145 cc	139 cc	139 cc
2900 rpm	2900 rpm	2900 rpm	2900 rpm	2900 rpm
1 L	1 L	0.95 L	0.90 L	0.75 L
0.55 L	0.55 L	0.40 L	0.50 L	0.50 L
Self-propelled	Self-propelled	Self-propelled	Self-propelled	Self-propelled
200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread	200/280mm grooved wheels on ball bearings with soft tread
51 cm	51 cm	46 cm	46 cm	46 cm
Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge	Collecting, Mulching, Side discharge, Rear discharge
1800 m <sup>2</sup>	1800 m <sup>2</sup>	1200 m <sup>2</sup>	1200 m <sup>2</sup>	1200 m <sup>2</sup>
Centralized	Centralized	Centralized	Centralized	Centralized
6 positions	6 positions	6 positions	6 positions	6 positions
22 - 80 mm	22 - 80 mm	22 - 80 mm	22 - 80 mm	22 - 80 mm
Hybrid with warn	Hybrid with warn	Hybrid with warn	Hybrid with warn	Hybrid with warn
60 L	60 L	60 L	60 L	60 L
Galvanized steel	Galvanized steel	Galvanized steel	Galvanized steel	Galvanized steel
Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip	Fulcrum + soft grip
Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes
Electric start by button	Recoil	Recoil	Electric start by button	Recoil
33 kg	33 kg	33 kg	32 kg	30 kg
2L0536548/ST2	2L0536848/ST2	2L0487838/ST2	2L0486548/ST2	2L0486848/ST2



# Corded lawn mowers



## Combi

340c

336c

Level	Essential	Essential
Series	3	3
POWER		
Power source	Electric	Electric
Power	1.6 KW	1.4 KW
DRIVING		
Driving	Push	Push
Wheels	150/250 mm grooved wheels	140/170 mm grooved wheels
MOWING		
Cutting width	38 cm	34 cm
Cutting method	Collecting, Mulching, Rear discharge	Collecting, Mulching, Rear discharge
Maximum working area	600 m <sup>2</sup>	400 m <sup>2</sup>
Cutting height adjustment	Centralized	Centralized
Cutting height positions	6 positions	6 positions
Cutting height range	25 - 75 mm	25 - 75 mm
Collector type	Textile	Textile
Collector capacity	40 L	35 L
Deck material	Polypropylene	Polypropylene
COMFORT		
Handlebar type	Flat with cam locks and comfort switch + soft grip	Flat with cam locks and comfort switch + soft grip
Adjustable handlebar	Yes	Yes
Foldable handlebar	Yes	Yes
Product weight	13 kg	11 kg
Art. N.	294380068/ST2	294340068/ST1

## MOWING

# Push cylinder mowers



SCM	240 R	440 FS
Level	Essential	Essential
POWER		
Power source	Push	Push
DRIVING		
Driving	Push	Push
MOWING		
Cutting width	40 cm	40 cm
Cutting method	Cylinder (helical cut)	Cylinder (helical cut)
Maximum working area	50 m²	50 m²
Cutting height adjustment	2 levers	Centralized by lever
Cutting height positions	3 positions	9 positions
Cutting height range	25 - 60 mm	25 - 76 mm
Blade type	Helical	Helical
Blade material	Steel	Steel
Number of blades	5	5
Number of spiders	4	4
Grass ejection	Rear	Front
COMFORT		
Handlebar type	Free adaptable	Free adaptable
Product weight	10.50 kg	17.20 kg
Art. N.	290401208/S15	290401608/S15



Grass collector	SCM 240 R*	SCM 440 FS*
Collector type	Textile	Textile
Capacity	18 L	20 L
Product weight	0.80 kg	1.20 kg
Art. N.	290409218/S15	290409618/S15

\*Separately available

# Battery axial mowers



## Gyro

700e

500e

Level

Experience

Experience

Series

7

5

### POWER

Power source

Lithium-ion battery

Lithium-ion battery

Battery capacity

64 Ah

40 Ah

Power

3300 Wh

2000 Wh

Maximum working area

8000 m<sup>2</sup>5000 m<sup>2</sup>

Battery kit

Included

Included

### MOWING

Main cutting method

Side discharge

Side discharge

Cutting width

108 cm

98 cm

Cutting height positions

8 positions

8 positions

Cutting height range

25 - 105 mm

25 - 105 mm

Cutting height adjustment

Manual

Manual

Transmission method

Drive-by-wire

Drive-by-wire

Transmission type

Stiga eMotion (Drive-By-Wire)

Stiga eMotion (Drive-By-Wire)

Traction

Rear-wheel drive

Rear-wheel drive

Maximum speed forward

12 Km/h

11 Km/h

Minimum uncut radius

0

0

Bluetooth connectivity

Yes as standard

Yes as standard

Maximum slope

15°

15°

### COMFORT

Seat type

Comfort with high back support and armrests

Comfort with low back support

Rear wheel size

18x8.50-8

18x8.50-8

Front wheel size

11x4.00-5

11x4.00-5

Dashboard

Yes, with Led

Yes, with display

Headlights

Led

Led

Art. N.

2F7063605/ST1

2F7062505/ST1

# Petrol front mowers



Park Pro	900 WX	900 AWX
Level	Expert	Expert
Series	9	9
POWER		
Power source	Petrol	Petrol
Power	14.3 kW	15.4 kW
Engine Brand	Honda	Honda
Engine model	GXV 630	GXV 690
Displacement	688 cc	688 cc
Engine rotation speed	3200 rpm	3200 rpm
Fuel tank capacity	15 L	15 L
Maximum working area	12500 m <sup>2</sup>	13000 m <sup>2</sup>
MOWING		
Cutting method	Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge
Cutting width	110 - 125 cm	110 - 125 cm
Cutting height adjustment	Electric	Electric
COMFORT		
Deck lift	Hydraulic	Hydraulic
PTO engagement	Electromagnetic	Electromagnetic
Traction	Four-wheel drive	Four-wheel drive
Transmission type	Hydrostatic	Hydrostatic
Steering type	Articulated (50/50)	Articulated (50/50)
Power assisted steering	Hydro piston	Hydro piston
Seat type	Comfort with high back support	Comfort with high back support
Front wheel size	17x8.00-8	17x8.00-8
Rear wheel size	17x8.00-8	17x8.00-8
Headlights	Led	Led
Dashboard	Yes with display	Yes with display
Bluetooth connectivity	Not available	Not available
Auxiliary hydraulic outlets	No	Yes
Art. N.	2F6430831/ST2	2F6430931/ST2



# Petrol front mowers



Park	900 WX	700 WX	700 W	500 W
Level	Expert	Experience	Experience	Experience
Series	9	7	7	5
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Power	11.82 kW	13.10 kW	13.10 kW	11.90 kW
Engine Brand	Briggs & Stratton	STIGA	STIGA	STIGA
Engine model	Vanguard 18	ST 600 Twin Powered by STIGA	ST 600 Twin Powered by STIGA	ST 550 Twin Powered by STIGA
Displacement	570 cc	586 cc	586 cc	586 cc
Engine rotation speed	3200 rpm	3200 rpm	3200 rpm	3200 rpm
Fuel tank capacity	12 L	12 L	12 L	12 L
Maximum working area	9500 m <sup>2</sup>	8500 m <sup>2</sup>	8000 m <sup>2</sup>	7000 m <sup>2</sup>
MOWING				
Cutting method	Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge
Cutting width	95 - 125 cm	95 - 125 cm	95 - 125 cm	95 - 110 cm
Cutting height adjustment	Electric	Electric	Electric	Electric
COMFORT				
Deck lift	Manual	Manual	Manual	Manual
PTO engagement	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
Traction	Four-wheel drive	Four-wheel drive	Rear-wheel drive	Rear-wheel drive
Transmission type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Steering type	Articulated (50/50)	Articulated (50/50)	Articulated (50/50)	Articulated (50/50)
Power assisted steering	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Seat type	Comfort with high back support	Comfort with high back support	Comfort with high back support	Comfort
Front wheel size	16x7.50-8	16x7.50-8	16x7.50-8	16x7.50-8
Rear wheel size	16x7.50-8	16x7.50-8	16x7.50-8	16x7.50-8
Headlights	LED – Advanced	LED – Advanced	LED – Advanced	Led
Dashboard	Yes	Yes	Yes	Yes – compact
Bluetooth connectivity	Yes as standard	Yes as standard	Yes as standard	Optional
Auxiliary hydraulic outlets	No	No	No	No
Art. N.	2F6230625/ST2	2F6230745/ST2	2F6220745/ST2	2F6120645/ST2



500 WX	500	300 M	300
<b>Experience</b>	<b>Experience</b>	<b>Essential</b>	<b>Essential</b>
<b>5</b>	<b>5</b>	<b>3</b>	<b>3</b>
Petrol	Petrol	Petrol	Petrol
11.90 kW	8.10 kW	7.10 kW	8.10 kW
STIGA	STIGA	STIGA	STIGA
ST 550 Twin Powered by STIGA	ST 450 Powered by STIGA	ST 400 Powered by STIGA	ST 450 Powered by STIGA
586 cc	432 cc	414 cc	432 cc
3200 rpm	3200 rpm	3200 rpm	3200 rpm
12 L	12 L	4.2 L	4.2 L
7500 m <sup>2</sup>	4500 m <sup>2</sup>	2500 m <sup>2</sup>	3000 m <sup>2</sup>
Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge	Combi - switch between Multiclip mulching and rear discharge
95 - 125 cm	95 - 100 cm	85 cm	85 - 95 cm
Electric	Electric	Manual	Electric
Manual	Manual	Manual	Manual
Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
Four-wheel drive	Rear-wheel drive	Rear-wheel drive	Rear-wheel drive
Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Articulated (50/50)	Articulated (50/50)	Articulated	Articulated
Hydraulic	Hydraulic	Not available	Not available
Comfort	Comfort	Standard	Standard
16x7.50-8	16x7.50-8	14.3x5.60-8	14.3x5.60-8
16x7.50-8	16x7.50-8	14.3x5.60-8	14.3x5.60-8
Led	No	No	No
Yes – compact	Yes – compact	No	No
Optional	Optional	Not available	Not available
No	No	No	No
2F6130645/ST2	2F6120545/ST2	2F5820241/S16	2F5820421/ST2

# Park deck compatibility



	Combi Pro 125 Q PLUS	Combi Pro 110 Q PLUS	Combi 100 Q PLUS	Combi 95 Q PLUS	Combi 95 Q	Combi 85 M Q
Park Pro 900 AWX	✘	✔				
Park Pro 900 WX	✘	✔				
Park 900 WX	✘	✔	✔	✔		
Park 700 WX	✔	✘	✔	✔		
Park 700 W	✔	✘	✔	✔		
Park 500 WX	✔	✔	✘	✔		
Park 500 W		✔	✘	✔		
Park 500			✔	✘		
Park 300					✘	✔
Park 300 M						✘
Art. N.	2D6312521/ST2	2D6311021/ST2	2D6210021/ST2	2D6209521/ST2	2D5809521/ST2	2D5808511/ST2



Suggested combination



Compatible combination



Only in combination with rear ballast



**STIGA QUICKFLIP PLUS TECHNOLOGY**  
allows you to easily raise the deck for washing and maintenance with minimal effort.  
**Gear wheel-pin system, carefully designed to grant maximum safety while deck is lifted.**



**STIGA QUICKFLIP TECHNOLOGY**  
allows you to easily raise the deck for washing and maintenance with minimal effort.

## MOWING

# Petrol zero turn



	ZT 7132 T	ZT 5132 T
Level	Experience	Experience
Series	7	5
POWER		
Power source	Petrol	Petrol
Power	16 kW	16.5 Kw
Engine Brand	Kawasaki	Kawasaki
Engine model	FR691	FR691
Displacement	726 cc	726 cc
Engine rotation speed	2950 rpm	3150 rpm
Fuel tank capacity	19 L	10.50 L
Maximum working area	16000 m²	12500 m²
Traction	Rear-wheel drive	Rear-wheel drive
Transmission type	Hydrostatic	Hydrostatic
Maximum speed forward	13 Km/h	11.30 Km/h
Hour meter	Yes	Yes
MOWING		
Cutting method	Side discharge	Side discharge
Cutting width	132 cm	132 cm
Cutting height adjustment	Manual	Manual
Cutting height range	38 -127 mm	38 - 114 mm
Deck Construction	Fabricated	Fabricated
Deck lift	Manual	Manual
Number of blades	3	3
COMFORT		
Steering type	Dual levers	Dual levers
Seat type	STIGA comfort plus with padded armrests	STIGA comfort plus with armrests
Dashboard	No	No
PTO engagement	Electromagnetic	Electromagnetic
Front wheel size	22x10.50-12	11x4.00-5
Rear wheel size	13x6.50-6	18x8.50-8
Art. N.	2F1020861/ST1	2F1020821/S17



# Battery tractors



## Tornado

	7108e	598e	398e
Level	Experience	Experience	Essential
Series	7	5	3
POWER			
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery capacity	64 Ah	40 Ah	30 Ah
Voltage	48 V	48 V	48 V
Battery kit	Included	Included	Included
Battery charger	Single fast	Single fast	Single fast
Charging system	External charger	External charger	External charger
Charging time	3.5 h	2.45 h	2 h
Transmission method	Pedal-operated	Pedal-operated	Pedal-operated
Transmission type	Electric	Electric	Electric
MOWING			
Cutting method	Side discharge	Side discharge	Side discharge
Cutting width	108 cm	98 cm	98 cm
Cutting height adjustment	Electric	Manual with lever	Manual with lever
Cutting height positions	Variable	7 positions	7 positions
Cutting height range	25 - 80 mm	25 - 80 mm	25 - 80 mm
Blade engagement type	Electric	Electric	Electric
Blade type	Mulching	Mulching	Mulching
Maximum working area	7500 m <sup>2</sup>	4500 m <sup>2</sup>	3500 m <sup>2</sup>
Mulching kit	Optional	Optional	Optional
Front wheel size	15x6.00-6	15x6.00-6	15x6.00-6
Rear wheel size	18x8.50-8	18x8.50-8	18x8.50-8
Number of blades	2	2	2
Reverse mowing	Yes	Yes	Yes
COMFORT			
Dashboard	Yes with display	Yes with LED	Yes with LED
Headlights	Led	Led	Led
Washing link	Yes	Yes	Yes
Bluetooth connectivity	Yes as standard	Yes as standard	Yes as standard
USB plug	1	1	1
Art. N.	2T1270481/ST2	2T0665481/ST2	2T0660481/ST2



## Estate

798e

584e

384e

Swift 372e

Level

Experience

Experience

Essential

Essential

Series

7

5

3

3

### POWER

Power source

Lithium-ion battery

Lithium-ion battery

Lithium-ion battery

Lithium-ion battery

Battery capacity

64 Ah

40 Ah

30 Ah

2 x 5 Ah + 2 x 7,5 Ah

Voltage

48 V

48 V

48 V

48 V

Battery kit

Included

Included

Included

Included

Battery charger

Single fast

Single fast

Single fast

Dual fast

Charging system

External charger

External charger

External charger

External charger

Charging time

3.5 h

2.45 h

2 h

3 h

Transmission method

Pedal-operated

Pedal-operated

Pedal-operated

Pedal-operated

Transmission type

Electric

Electric

Electric

Electric

### MOWING

Cutting method

Collecting

Collecting

Collecting

Collecting

Cutting width

98 cm

84 cm

84 cm

72 cm

Cutting height adjustment

Electric

Manual with lever

Manual with lever

Manual with lever

Cutting height positions

Variable

7 positions

7 positions

6 positions

Cutting height range

25 - 80 mm

25 - 80 mm

25 - 80 mm

30 - 80 mm

Blade engagement type

Electric

Electric

Electric

Electric

Blade type

Winged

Winged

Winged

Winged - Mulching

Maximum working area

7000 m<sup>2</sup>

4000 m<sup>2</sup>

3000 m<sup>2</sup>

2000 m<sup>2</sup>

Mulching kit

Optional

Optional

Optional

Optional

Front wheel size

15x6.00-6

15x6.00-6

15x6.00-6

13x5.00-6

Rear wheel size

18x8.50-8

18x8.50-8

18x8.50-8

15x6.00-6

Number of blades

2

2

2

2

Reverse mowing

Yes

Yes

Yes

Yes

### COMFORT

Dashboard

Yes with display

Yes with LED

Yes with LED

Yes with LED

Headlights

Led

Led

Led

Led

Washing link

Yes

Yes

Yes

Yes

Bluetooth connectivity

Yes as standard

Yes as standard

Yes as standard

Yes as standard

USB plug

1

1

1

1

Art. N.

2T2800481/ST2

2T2205481/ST2

2T2200481/ST2

2T0250481/ST1

# Petrol tractors



## Tornado

	9121 WX	9121 W	7108 W	5108 W
Level	Expert	Expert	Experience	Experience
Series	9	9	7	5
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Displacement	688 cc	688 cc	635 cc	586 cc
Engine Brand	Honda	Honda	STIGA	STIGA
Engine model	GXV 690	GXV 630	ST 650 Twin Powered by STIGA	ST 550 Twin Powered by STIGA
Engine rotation speed	2700 rpm	2700 rpm	2700 rpm	2800 rpm
Fuel tank capacity	15 L	15 L	15 L	6 L
Transmission method	Pedal-operated	Pedal-operated	Pedal-operated	Pedal-operated
Transmission type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Number of cylinders	2	2	2	2
MOWING				
Cutting method	Side discharge	Side discharge	Side discharge	Side discharge
Cutting width	121 cm	121 cm	108 cm	108 cm
Cutting height adjustment	Manual with control knob	Manual with lever	Manual with lever	Manual with lever
Cutting height positions	9 positions	7 positions	7 positions	7 positions
Cutting height range	25 - 100 mm	30 - 90 mm	30 - 90 mm	25 - 80 mm
Blade engagement type	Electric	Electric	Electric	Electric
Maximum working area	9500 m <sup>2</sup>	8500 m <sup>2</sup>	7000 m <sup>2</sup>	6500 m <sup>2</sup>
Mulching kit	Optional	Optional	Optional	Optional
Front wheel size	16x6.00-8	16x6.00-8	15x6.00-6	15x6.00-6
Rear wheel size	20x10.00-10	20x10.00-10	20x10.00-10	20x10.00-10
Number of blades	3	3	2	2
Reverse mowing	Yes	Yes	Yes	Yes
Bumper	Yes	Yes	Yes	Yes
COMFORT				
Dashboard	Yes with smart widescreen display	Yes with smart widescreen display	Yes with multifunctional display	No
Headlights	LED – Advanced	LED – Advanced	LED – Advanced	Led
Washing link	Yes	Yes	Yes	Yes
Cruise control	Yes	Yes	No	No
Art. N.	2T3040381/ST2	2T1945381/ST2	2T1845481/ST2	2T1220481/ST2



5108	598	398	398 M
<b>Experience</b>	<b>Experience</b>	<b>Essential</b>	<b>Essential</b>
<b>5</b>	<b>5</b>	<b>3</b>	<b>3</b>
Petrol	Petrol	Petrol	Petrol
452 cc	452 cc	432 cc	352 cc
STIGA	STIGA	STIGA	STIGA
ST 500 Powered by STIGA	ST 500 Powered by STIGA	ST 450 Powered by STIGA	ST 350 Powered by STIGA
2800 rpm	2800 rpm	2800 rpm	2800 rpm
6 L	6 L	6 L	6 L
Pedal-operated	Pedal-operated	Pedal-operated	Lever-operated
Hydrostatic	Hydrostatic	Hydrostatic	Mechanical
1	1	1	1
Side discharge	Side discharge	Side discharge	Side discharge
108 cm	98 cm	98 cm	98 cm
Manual with lever	Manual with lever	Manual with lever	Manual with lever
7 positions	7 positions	7 positions	7 positions
25 - 80 mm	25 - 85 mm	25 - 80 mm	25 - 80 mm
Electric	Electric	Electric	Electric
6000 m <sup>2</sup>	5000 m <sup>2</sup>	5000 m <sup>2</sup>	4500 m <sup>2</sup>
Optional	Optional	Optional	Optional
15x6.00-6	15x6.00-6	15x6.00-6	15x6.00-6
18x8.50-8	18x8.50-8	18x8.50-8	18x8.50-8
2	2	2	2
Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes
No	No	No	No
Led	Led	Conventional	Conventional
Yes	Yes	Yes	Yes
No	No	No	No
2T1215481/ST1	2T0620481/ST1	2T0610481/ST1	2T0510481/ST3

# Petrol tractors



## Estate

	9122 WX	9102 WX	9122 W	9102 W
Level	Expert	Expert	Expert	Expert
Series	9	9	9	9
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Displacement	688 cc	688 cc	688 cc	688 cc
Engine Brand	Honda	Honda	Honda	Honda
Engine model	GXV 690	GXV 690	GXV 630	GXV 630
Engine rotation speed	2700 rpm	2500 rpm	2700 rpm	2500 rpm
Fuel tank capacity	10 L	10 L	8 L	8 L
Transmission method	Pedal-operated	Pedal-operated	Pedal-operated	Pedal-operated
Transmission type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Number of cylinders	2	2	2	2
MOWING				
Cutting method	Collecting	Collecting	Collecting	Collecting
Cutting width	122 cm	102 cm	122 cm	102 cm
Cutting height adjustment	Manual with control knob	Manual with control knob	Manual with lever	Manual with lever
Cutting height positions	9 positions	9 positions	7 positions	7 positions
Cutting height range	25 - 100 mm	25 - 100 mm	30 - 90 mm	30 - 90 mm
Blade engagement type	Electric	Electric	Electric	Electric
Maximum working area	9000 m <sup>2</sup>	8000 m <sup>2</sup>	8000 m <sup>2</sup>	7000 m <sup>2</sup>
Mulching kit	Optional	Optional	Optional	Optional
Front wheel size	16x6.00-8	16x6.00-8	15x6.00-6	15x6.00-6
Rear wheel size	20x10.00-10	20x10.00-10	18x8.50-8	18x8.50-8
Number of blades	2	2	2	2
Reverse mowing	Yes	Yes	Yes	Yes
Bumper	Yes	Yes	Yes	Yes
COMFORT				
Dashboard	Yes with smart widescreen display	Yes with smart widescreen display	Yes with smart widescreen display	Yes with smart widescreen display
Headlights	LED – Advanced	LED – Advanced	LED – Advanced	LED – Advanced
Washing link	Yes	Yes	Yes	Yes
Cruise control	Yes	Yes	Yes	Yes
Art. N.	2T1535381/ST2	2T1430381/ST2	2T1310381/ST2	2T0980381/ST2





7102 W	792 W	792	598 W
<b>Experience</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
<b>7</b>	<b>7</b>	<b>7</b>	<b>5</b>
Petrol	Petrol	Petrol	Petrol
635 cc	586 cc	452 cc	586 cc
STIGA	STIGA	STIGA	STIGA
ST 650 Twin Powered by STIGA	ST 600 Twin Powered by STIGA	ST 500 Powered by STIGA	ST 550 Twin Powered by STIGA
2400 rpm	2700 rpm	2800 rpm	2600 rpm
8 L	8 L	8 L	6 L
Pedal-operated	Pedal-operated	Pedal-operated	Pedal-operated
Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
2	2	1	2
Collecting	Collecting	Collecting	Collecting
102 cm	92 cm	92 cm	98 cm
Manual with lever	Manual with lever	Manual with lever	Manual with lever
7 positions	7 positions	7 positions	7 positions
30 - 90 mm	30 - 90 mm	30 - 90 mm	25 - 80 mm
Electric	Electric	Electric	Electric
6000 m²	5000 m²	4500 m²	5000 m²
Optional	Optional	Optional	Optional
15x6.00-6	15x6.00-6	15x6.00-6	15x6.00-6
18x8.50-8	18x8.50-8	18x8.50-8	18x8.50-8
2	2	2	2
Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes
Yes with multifunctional display	Yes with multifunctional display	Yes with multifunctional display	Yes with LED
LED – Advanced	LED – Advanced	LED – Advanced	Led
Yes	Yes	Yes	Yes
No	No	No	No
2T0980481/ST2	2T0785481/ST1	2T0780481/ST1	2T2630481/ST2

# Petrol tractors



Estate	598	584	384	384 M
Level	Experience	Experience	Essential	Essential
Series	5	5	3	3
POWER				
Power source	Petrol	Petrol	Petrol	Petrol
Displacement	452 cc	452 cc	432 cc	352 cc
Engine Brand	STIGA	STIGA	STIGA	STIGA
Engine model	ST 500 Powered by STIGA	ST 500 Powered by STIGA	ST 450 Powered by STIGA	ST 350 Powered by STIGA
Engine rotation speed	2600 rpm	2400 rpm	2400 rpm	2400 rpm
Fuel tank capacity	6 L	6 L	6 L	6 L
Transmission method	Pedal-operated	Pedal-operated	Pedal-operated	Lever-operated
Transmission type	Hydrostatic	Hydrostatic	Hydrostatic	Mechanical
Number of cylinders	1	1	1	1
MOWING				
Cutting method	Collecting	Collecting	Collecting	Collecting
Cutting width	98 cm	84 cm	84 cm	84 cm
Cutting height adjustment	Manual with lever	Manual with lever	Manual with lever	Manual with lever
Cutting height positions	7 positions	7 positions	7 positions	7 positions
Cutting height range	25 - 85 mm	25 - 80 mm	25 - 80 mm	25 - 80 mm
Blade engagement type	Electric	Electric	Electric	Electric
Maximum working area	4500 m²	3500 m²	3500 m²	3000 m²
Mulching kit	Optional	Optional	Optional	Optional
Front wheel size	15x6.00-6	15x6.00-6	15x6.00-6	15x6.00-6
Rear wheel size	18x8.50-8	18x8.50-8	18x8.50-8	18x8.50-8
Number of blades	2	2	2	2
Reverse mowing	Yes	Yes	Yes	Yes
Bumper	Yes	Yes	Yes	Yes
COMFORT				
Dashboard	Yes with LED	Yes with LED	Yes with LED	Yes with LED
Headlights	Led	Led	Conventional	Conventional
Washing link	Yes	Yes	Yes	Yes
Cruise control	No	No	No	No
Art. N.	2T2620481/ST2	2T2115481/ST1	2T2100481/ST1	2T2000481/ST3



## Combi

**372**

**166**

Level	<b>Essential</b>	<b>Essential</b>
Series	<b>3</b>	<b>1</b>
<b>POWER</b>		
Power source	Petrol	Petrol
Displacement	414 cc	224 cc
Engine Brand	STIGA	STIGA
Engine model	ST 400 Powered by STIGA	ST 250 ES Powered by STIGA
Engine rotation speed	2800 rpm	2450 rpm
Fuel tank capacity	4 L	3.80 L
Transmission method	Lever-operated	Pedal-operated
Transmission type	Hydrostatic	Hydrostatic
Number of cylinders	1	1
<b>MOWING</b>		
Cutting method	Collecting	Collecting, Side discharge
Cutting width	72 cm	66 cm
Cutting height adjustment	Manual with lever	Manual with lever
Cutting height positions	7 positions	6 positions
Cutting height range	30 - 80 mm	30 - 76 mm
Blade engagement type	Manual	Manual
Maximum working area	2500 m²	1500 m²
Mulching kit	Optional	Optional
Front wheel size	11x4.00-4	13x5.00-6
Rear wheel size	15x6.00-6	15x6.00-6
Number of blades	1	1
Reverse mowing	Yes	Yes
Bumper	No	No
<b>COMFORT</b>		
Dashboard	Yes with LED	No
Headlights	Conventional	No
Washing link	Yes	Yes
Cruise control	No	No
Art. N.	2T0210481/ST2	2T0070481/ST2

# Battery blowers



	BL 900e	BL 700e	BL 500e	BL 500e Kit
Level	<b>Expert</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
Series	<b>9</b>	<b>7</b>	<b>5</b>	<b>5</b>
<b>POWER</b>				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Power	0.9 kW	0.5 kW	0.65 kW	0.65 kW
Battery kit	Not included	Not included	Not included	Included
Voltage	48 V	48 V	48 V	48 V
Battery type	Lithium-ions	Lithium-ions	Lithium-ions	Lithium-ions
Lithium battery nominal energy	324 Wh	172.8 Wh	172.8 Wh	86.4 Wh
Battery capacity	7.5 Ah	4 Ah	4 Ah	2 Ah
Suggested battery capacity	2 x 7.5 Ah	4 Ah	4 Ah	4 Ah
Working time min (+/- 20%)	100 min	26 min	30 min	32 min
Motor type	Brushless	Brushless	Brushless	Brushless
<b>BLOWING</b>				
Maximum air volume	15.80 m³/min	11.60 m³/min	11.40 m³/min	11.40 m³/min
Maximum air speed	55 m/s	60 m/s	55 m/s	51.4 m/s
<b>COMFORT</b>				
Vibe Control System (VCS)	Yes	Yes	No	No
Harness	Backpack	Single	No	No
Soft grip handle	Yes	Yes	Yes	Yes
Guaranteed sound power level (LwA)	94 dB(A)	95 dB(A)	96 dB(A)	96 dB(A)
<b>TOOLS KIT</b>				
Battery charger	2 x Single standard	Single standard	Single standard	Single standard
Battery charger output current	1.5 A	1.5 A	1.5 A	1.5 A
Product weight	2.85 kg	2.76 kg	2.80 kg	3.64 kg
Art. N.	279500008/ST2	277500008/ST2	278500008/ST3	278502108/ST3

# and vacuum shredder



## BL 100e Kit

### Essential

1

Lithium-ion battery

0.28 kW

Included

20 V

Lithium-ions

72 Wh

4 Ah

4 Ah

40 min

With brushes

9 m³/min

32 m/s

No

No

No

92 dB(A)

Single standard

2 A

2.14 kg

271504108/ST2



## VS 100e Kit

### Essential

1

Level

Series

#### POWER

Power source

Lithium-ion battery

Power

0.6 kW

Battery kit

Included

Voltage

20 V

Lithium battery nominal energy

144 Wh

Battery capacity

2 x 4 Ah

Suggested battery capacity

2 x 4 Ah

Working time (+/- 20%)

23 min

Motor type

Brushless

#### BLOWING

Maximum air volume

9.6 m³/min

Maximum air speed

55 m/s

Vacuum function

Yes

Mulching ratio

10:1

Collector type

Textile

Collector capacity

45 L

Collector emptying

Manual

Blade material

Aluminium

#### COMFORT

Vibe Control System (VCS)

No

Harness

No

Soft grip handle

Yes

Guaranteed sound power level (LwA)

102 dB(A)

#### TOOLS KIT

Speed selector

Yes

Battery charger

Dual standard

Battery charger output current

3 A

Product weight

2 kg

Art. N.

271504198/ST1



# Petrol blowers



	BL 980 R	BL 530 V	BL 530
Level	<b>Expert</b>	<b>Experience</b>	<b>Experience</b>
Series	<b>9</b>	<b>5</b>	<b>5</b>
<b>POWER</b>			
Power source	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
Power	3.1 kW	0.8 kW	0.8 kW
Displacement	75.6 cc	27.6 cc	27.6 cc
Engine rotation speed	7000 rpm	7500 rpm	7500 rpm
Starter	Recoil	Recoil	Recoil
Primer	Yes	Yes	Yes
Choke	Manual with automatic return	Manual with automatic return	Manual with automatic return
Fuel tank capacity	2.10 L	0.45 L	0.45 L
<b>BLOWING</b>			
Maximum air volume	25 m³/min	10.2 m³/min	10.2 m³/min
Maximum air speed	100 m/s	72 m/s	72 m/s
Vacuum function	No	Yes	No
Collector type	-	Textile	-
Collector capacity	-	55 L	-
<b>COMFORT</b>			
Vibe Control System (VCS)	Yes	Yes	Yes
Harness	Backpack	Not included	Not included
Soft grip handle	Yes	Yes	Yes
Guaranteed sound power level (LwA)	112 dB(A)	109 dB(A)	109 dB(A)
Included tools kit	Screwdriver	Screwdriver	Screwdriver
Product weight	12.43 kg	4.96 kg	6.24 kg
Art. N.	255175102/ST1	255127002/ST1	255127092/ST2

CLEANING

# Corded blower



**BL 130c V**

Level	Essential
Series	1
POWER	
Power source	Electric
Power	2.6 kW
Motor type	Brushless
BLOWING	
Maximum air volume	7 m³/min
Maximum air speed	92 m/s
Vacuum function	Yes
Collector type	Textile
Collector capacity	45 L
COMFORT	
Vibe Control System (VCS)	No
Soft grip handle	Yes
Guaranteed sound power level (LwA)	98 dB(A)
Product weight	4.62 kg
Art. N.	255260002/ST1

# Corded high pressure cleaners



	HPS 650 RG	HPS 550 R	HPS 345 R	HPS 235 R	HPS 110
	Experience	Experience	Experience	Experience	Essential
POWER					
Power source	Electric	Electric	Electric	Electric	Electric
Max pressure	150 bar	150 bar	145 bar	135 bar	110 bar
Max rated flow	550 l/h	520 l/h	450 l/h	440 l/h	390 l/h
Max water inlet temperature	50 °C	50 °C	50 °C	50 °C	50 °C
Motor class	Induction	Induction	Induction	Universal	Universal
Pressure adjustment	Yes	No	No	No	No
Pressure gauge	Standard	No	No	No	No
CLEANING					
Detergent adjustment	Yes - rotating knob	Yes - rotating knob	No	No	No
Detergent device	Built-in tank (1,0 l)	Built-in tank (1,0 l)	Foam sprayer (0,4 l)	Foam sprayer (0,4 l)	Foam sprayer (0,3 l)
Accessory holder	Onboard storage - Back	Onboard storage - Back	Foldable front cover	Foldable front cover	Onboard storage - Back
Gun material	Metal with soft touch	Metal with soft touch	Plastic	Plastic	Plastic
Gun type	STIGA T5	STIGA T5	STIGA T3	STIGA T3	STIGA T1
COMFORT					
Ergonomic extra handle	Yes	Yes	No	No	No
Pump material	Brass	Brass	Aluminium	Aluminium	Aluminium
Pump mechanical system	Wobble plate	Wobble plate	Wobble plate	Wobble plate	Wobble plate
Self priming	Yes	Yes	Yes	Yes	Yes
Total stop system (TSS)	Yes	Yes	Yes	Yes	Yes
Transparent water filter	Yes	Yes	Yes	Yes	Yes
Nozzle cleaning pin	Yes	Yes	Yes	Yes	Yes
Piston material	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Pistons number	3	3	3	3	3
Cable storage	Yes	Yes	Yes	Yes	Yes
Cable storage type	Side cord holder	Side cord holder	Side cord holder	Side cord holder	Side cord holder
Electric cable length	5 m	5 m	5 m	5 m	5 m
Hose quick release pump outlet gun	No	No	Yes	Yes	Yes
Hose reel	Yes	Yes	Yes	Yes	No
HP hose material	Steel reinforced	Steel reinforced	Steel reinforced	Supersoft	Textile PVC with reduced diameter
High pressure hose length	12 m	10 m	9 m	6 m	5 m
Product weight	27.70 kg	24.70 kg	17.30 kg	11.50 kg	5.50 kg
Art. N.	2C1502804/ST1	2C1502504/ST1	2C1452103/ST2	2C1351801/ST2	2C1101401/ST1

# Petrol sweepers



	SWS 800 GE	SWS 600 GE	SWS 800 G	SWS 600 G
Level	Experience	Experience	Essential	Essential
POWER				
Power source	Petrol	Petrol	Petrol 4-stroke	Petrol 4-stroke
Power	4.4 kW	4.4 kW	4.4 kW	4.4 kW
Engine Brand	STIGA	STIGA	STIGA	STIGA
Engine model	SM70	SM70	SM70	SM70
Displacement	212 cc	212 cc	212 cc	212 cc
Maximum engine speed	3600 rpm	3600 rpm	3600 rpm	3600 rpm
Fuel tank capacity	3 L	3 L	3 L	3 L
Transmission type	Friction disc	Friction disc	Friction disc	Friction disc
SWEEPING				
Number of gears	6 forward + 2 reverse	6 forward + 2 reverse	6 forward + 2 reverse	6 forward + 2 reverse
Working width	80 cm	60 cm	80 cm	60 cm
Brush diameter	345 mm	345 mm	345 mm	345 mm
Brush height adjustment	Yes - Pivoting wheels	Yes - Pivoting wheels	Yes - Pivoting wheels	Yes - Pivoting wheels
Max angle adjustment, left/right	15°/15°	15°/15°	15°/15°	15°/15°
Air filter type	Sponge + oil bath	Sponge + oil bath	Sponge + oil bath	Sponge + oil bath
Brush material	Nylon	Nylon	Nylon	Nylon
Sweeping type	Forward	Forward	Forward	Forward
COMFORT				
Electric start	Yes	Yes	No	No
Product weight	70 kg	65 kg	70 kg	65 kg
Art. N.	219802532/ST1	219602532/ST1	219802532/S17	219602532/S17

# Push sweepers



	SWP 577	SWP 475	SWP 355
Level	Experience	Experience	Essential
POWER			
Power source	Push	Push	Push
CLEANING			
Rotating brush roller	Yes	Yes	Yes
Rotating brush roller length	46 cm	46 cm	40 cm
Sweeping performance	3000 m <sup>2</sup> /h	2900 m <sup>2</sup> /h	1600 m <sup>2</sup> /h
Sweeping type	Rear collection	Rear collection	Rear collection
Brush diameter	410 mm	410 mm	300 mm
Brush height adjustment	Yes - 8 steps	Yes - 8 steps	Yes - 3 steps
Brush material	Nylon	Nylon	Nylon
Collector capacity	50 L	50 L	20 L
Collector type	Plastic	Plastic	Plastic
Gear protection cover	Yes	No	No
COMFORT			
Adjustable handlebar	Yes	No	Yes
Transport handle	No	No	Yes
Handlebar type	Ergonomic	Flat	Ergonomic
Flexible seals	Yes	No	No
Product weight	14.60 kg	11.20 kg	7.20 kg
Art. N.	2W0775012/ST1	2W0755011/ST1	2W0552511/ST1

# Battery snow throwers



	ST 700e	ST 700e Kit	ST 300e	ST 300e Kit
Level	Experience	Experience	Essential	Essential
Series	7	7	3	3
POWER				
Platform	One stage	One stage	Snow shovel	Snow shovel
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery capacity	4 Ah	4 Ah	2 Ah	2 Ah
Power	1000 W	1000 W	450 W	450 W
Battery Voltage	48 V	48 V	48 V	48 V
Battery kit	Not included	Included	Not included	Included
THROWING				
Auger width	50 cm	50 cm	30 cm	30 cm
Auger house height	30 cm	30 cm	20 cm	20 cm
Auger diameter	17 cm	17 cm	15 cm	15 cm
Auger type	Plastic	Plastic	Plastic	Plastic
Chute control	Manual - Center crank	Manual - Center crank	-	-
Chute rotation	180°	180°	-	-
Deflector control	Manual - On chute	Manual - On chute	Manual	Manual
Deflector material	Plastic	Plastic	Plastic	Plastic
Throwing performance	6 m	6 m	5 m	5 m
Steering type	Manual	Manual	-	-
Wheel type	Plastic, Stiga design	Plastic, Stiga design	-	-
COMFORT				
Headlights	Led	Led	-	-
Transport handle	Yes	Yes	Yes	Yes
One hand grip	Yes	Yes	-	-
Product weight	14.50 kg	14.50 kg	14.50 kg	14.50 kg
Art. N.	2S1500101/ST1	2S1500108/ST1	2S1330101/ST1	2S1330108/ST1



# Petrol snow throwers



	ST 7276 PH	ST 6272 P TRAC	ST 5266 P TRAC
Level	<b>Expert</b>	<b>Experience</b>	<b>Experience</b>
<b>POWER</b>			
Platform	Two Stages	Two Stages	Two Stages
Power source	Petrol	Petrol	Petrol
Power	9 kW	7.8 kW	6.2 kW
Engine Brand	STIGA	STIGA	STIGA
Engine model	WS 420	WS 380	WS 300
Displacement	420 cc	375 cc	302 cc
Engine rotation speed	3600 rpm	3600 rpm	3600 rpm
Electric start	Yes	Yes	Yes
Fuel tank capacity	5.50 L	5.50 L	4 L
<b>THROWING</b>			
Auger width	76 cm	72 cm	66 cm
Auger house height	53 cm	53 cm	53 cm
Auger diameter	37.50 cm	37.50 cm	37.50 cm
Auger type	Steel - Saw toothed	Steel - Saw toothed	Steel - Saw toothed
Chute control	Electric - Dash mounted switch	Manual - Dash mounted crank	Manual - Dash mounted crank
Deflector control	Electric - Dash mounted switch	Manual - Dash mounted crank	Manual - Dash mounted crank
Impeller diameter	37.50 cm	37.50 cm	37.50 cm
Throwing performance	15 m	13 m	12 m
Number of gears	No	6 forward + 2 reverse	6 forward + 2 reverse
Transmission type	Hydrostatic	Friction disc	Friction disc
Steering type	2 trigger - steerable	1 trigger - steerable	1 trigger - steerable
<b>COMFORT</b>			
Central operation panel	Yes	Yes	Yes
Headlights	Led	Led	Led
One hand grip	Yes	Yes	Yes
Overload protection	Shear bolts	Shear bolts	Shear bolts
Heated handgrip	Yes	Yes	Yes
Product weight	134 kg	108.50 kg	108.50 kg
Art. N.	2S2767711/ST1	2S2726611/ST1	2S2666611/ST1



ST 5266 P	ST 5262 P	ST 4262 P
Experience	Experience	Essential
Two Stages	Two Stages	Two Stages
Petrol	Petrol	Petrol
6.2 kW	5.2 kW	4.4 kW
STIGA	STIGA	STIGA
WS 300	WS 250	WS 210
302 cc	252 cc	212 cc
3600 rpm	3600 rpm	3600 rpm
Yes	Yes	Yes
4 L	3.20 L	3 L
66 cm	62 cm	62 cm
53 cm	51 cm	51 cm
37.50 cm	30 cm	30 cm
Steel - Saw toothed	Steel - Saw toothed	Steel - Saw toothed
Manual - Dash mounted crank	Manual - Dash mounted crank	Manual - Dash mounted crank
Manual - Dash mounted crank	Manual - Dash mounted crank	Manual - Dash mounted crank
37.50 cm	30 cm	30 cm
12 m	11 m	8 m
6 forward + 2 reverse	6 forward + 2 reverse	6 forward + 2 reverse
Friction disc	Friction disc	Friction disc
Automatic Diff.lock release	Automatic Diff.lock release	Standard
Yes	Yes	Yes
Led	Led	No
Yes	Yes	Yes
Shear bolts	Shear bolts	Shear bolts
Yes	Yes	No
96 kg	95 kg	90 kg
2S2664611/ST1	2S2624511/ST1	18-2841-31

# Battery brushcutters



	BC 900e B	BC 700e B	BC 700e	BC 500e
Level	<b>Expert</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
Series	<b>9</b>	<b>7</b>	<b>7</b>	<b>5</b>
<b>POWER</b>				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery kit	Not included	Not included	Not included	Not included
Voltage	48 V	48 V	48 V	48 V
Lithium battery nominal energy	324 Wh	172.80 Wh	172.80 Wh	172.80 Wh
Battery capacity	7.5 Ah	4 Ah	4 Ah	4 Ah
Suggested battery capacity	2 x 7.5 Ah	4 Ah	4 Ah	4 Ah
Working time (+/- 20%)	70 min	30 min	30 min	30 min
Motor type	Brushless	Brushless	Brushless	Brushless
<b>TRIMMING</b>				
Cutting width	43 cm	38 cm	38 cm	38 cm
Cutting angle	Fixed	Fixed	Fixed	Fixed
Nylon head type	Bump & Work dual line - Easy load	Bump & Work dual line - Easy load	Bump & Work dual line - Easy load	Tap & Go dual line easy load
Nylon line length	4 m	4 m	4 m	4 m
Blade type	3T ARC	3T ARC	3T ARC	3 T
<b>COMFORT</b>				
Vibe Control System (VCS)	Yes	Yes	No	No
Harness	Double Comfort	Double Comfort	Single	Single
Soft grip handle	Yes	Yes	Yes	Yes
Handle type	Bike	Bike	Loop Adjustable	Loop
Shaft type	Straight	Straight	Straight	Straight
Shaft tube diameter	25.40 mm	25 mm	25 mm	25.40 mm
<b>TOOLS KIT</b>				
Battery charger	Single fast	Single standard	Single standard	Single standard
Battery charger output current	3 A	1.5 A	1.5 A	1.5 A
Product weight	7.30 kg	6 kg	4.70 kg	4.70 kg
Art. N.	279210008/ST2	277210008/ST2	277200008/ST2	278200008/ST3

# Battery lawn trimmers



	GT 500e	GT 500e Kit	GT 100e Kit
Level	<b>Experience</b>	<b>Experience</b>	<b>Essential</b>
Series	<b>5</b>	<b>5</b>	<b>1</b>
<b>POWER</b>			
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery kit	Not included	Included	Included
Voltage	48 V	48 V	20 V
Lithium battery nominal energy	86.40 Wh	86.40 Wh	36 Wh
Battery capacity	2 Ah	2 Ah	2 Ah
Suggested battery capacity	2 Ah	2 Ah	2 Ah
Working time (+/- 20%)	20 min	20 min	20 min
Motor type	With brushes	With brushes	With brushes
<b>TRIMMING</b>			
Cutting width	30 cm	30 cm	25 cm
Cutting angle	Fixed + edge trimmer function	Fixed + edge trimmer function	Adjustable
Nylon head type	Automatic dual line	Automatic dual line	Automatic single line
Nylon line length	4 m	4 m	4 m
Blade type	-	-	-
<b>COMFORT</b>			
Vibe Control System (VCS)	No	No	No
Harness	No	No	No
Soft grip handle	Yes	Yes	No
Handle type	Loop Adjustable	Loop Adjustable	Loop
Shaft type	Telescopic	Telescopic	Telescopic
Shaft tube diameter	25.40 mm	25.40 mm	26 mm
<b>TOOLS KIT</b>			
Battery charger	Single standard	Single standard	Single standard
Battery charger output current	1.5 A	1.5 A	2 A
Product weight	3.05 kg	3.93 kg	2.20 kg
Art. N.	278100008/ST3	278102108/ST3	271102108/ST2

# Petrol brushcutters



	BC 760 B	BC 750 R	BC 750 B	BC 740 B
Level	Experience	Experience	Experience	Experience
Series	7	7	7	7
POWER				
Power source	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
Power	1.7 kW	1.5 kW	1.5 kW	1.2 kW
Displacement	52.8 cc	44.8 cc	44.8 cc	35.3 cc
Engine rotation speed	7500 rpm	9500 rpm	7500 rpm	3000 rpm
Primer	Yes	Yes	Yes	Yes
Choke	Automatic	Automatic	Automatic	Manual
Fuel tank capacity	0.80 L	0.80 L	0.80 L	0.60 L
TRIMMING				
Cutting width	45 cm	45 cm	45 cm	43 cm
Nylon head type	Bump & Work dual line	Bump & Work dual line	Bump & Work dual line	Bump & Work dual line
Nylon line length	4 m	4 m	4 m	4 m
Blade type	3T ARC	3T ARC	3T ARC	3T ARC
COMFORT				
Vibe Control System (VCS)	Yes	Yes	Yes	Yes
Harness	Double Comfort	Racksack	Double Comfort	Double Comfort
Soft grip handle	Yes	Yes	Yes	Yes
Handle type	Bike	Loop	Bike	Bike
Shaft type	Straight	Flexible	Straight	Straight
Shaft tube diameter	30 mm	28 mm	30 mm	28 mm
Product weight	9.60 kg	12.90 kg	9.60 kg	8.30 kg
Art. N.	283524008/ST2	283423008/ST2	283424008/ST2	283321008/ST2



BC 730 B	BC 730	BC 555 B	BC 555 R
<b>Experience</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
<b>7</b>	<b>7</b>	<b>5</b>	<b>5</b>
Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
1 kW	1 kW	1.55 kW	1.55 kW
25.4 cc	25.4 cc	51.7 cc	51.7 cc
6000 rpm	6000 rpm	9500 rpm	9500 rpm
Yes	Yes	Yes	Yes
Manual	Manual	Manual with automatic return	Manual with automatic return
0.45 L	0.45 L	1 L	1 L
44 cm	43 cm	45 cm	45 cm
Bump & Work dual line	Bump & Work dual line	Bump & Work dual line	Bump & Work dual line
4 m	4 m	4 m	4 m
3 T	3 T	3 T	3 T
No	No	Yes	Yes
Single	Single	Double	Racksack
Yes	Yes	Yes	Yes
Bike	Loop	Bike	Loop
Straight	Straight	Straight - Forest type	Flexible
24 mm	24 mm	28 mm	26 mm
5.70 kg	5.50 kg	9 kg	11.70 kg
283221008/ST1	283220008/ST1	287421002/ST1	287422002/ST1



# Petrol brushcutters



	BC 545 B	BC 545	BC 535 B	BC 535
Level	Experience	Experience	Experience	Experience
Series	5	5	5	5
POWER				
Power source	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
Power	1.25 kW	1.25 kW	0.9 kW	0.9 kW
Displacement	42.7 cc	42.7 cc	32.6 cc	32.6 cc
Engine rotation speed	9500 rpm	9500 rpm	11000 rpm	11000 rpm
Primer	Yes	Yes	Yes	Yes
Choke	Manual with automatic return	Manual with automatic return	Manual with automatic return	Manual with automatic return
Fuel tank capacity	1 L	1 L	0.80 L	0.80 L
TRIMMING				
Cutting width	45 cm	45 cm	43 cm	43 cm
Nylon head type	Bump & Work dual line	Bump & Work dual line	Bump & Work dual line	Bump & Work dual line
Nylon line length	4 m	4 m	4 m	4 m
Blade type	3 T	3 T	3 T	3 T
COMFORT				
Vibe Control System (VCS)	Yes	Yes	Yes	Yes
Harness	Double	Double	Double	Single
Soft grip handle	Yes	Yes	Yes	Yes
Handle type	Bike	Loop	Bike	Loop
Shaft type	Straight - Forest type	Straight	Straight - Forest type	Straight
Shaft tube diameter	28 mm	26 mm	26 mm	26 mm
Product weight	9 kg	8.60 kg	8.60 kg	8.30 kg
Art. N.	287321002/ST1	287320002/ST1	287221002/ST1	287220002/ST1



BC 330 AB	BC 330 A
<b>Essential</b>	<b>Essential</b>
<b>3</b>	<b>3</b>
Petrol 2-stroke	Petrol 2-stroke
0.7 kW	0.7 kW
25.4 cc	25.4 cc
11000 rpm	11000 rpm
Yes	Yes
Manual	Manual
0.65 L	0.65 L
43 cm	43 cm
Bump & Work dual line	Bump & Work dual line
4 m	4 m
3 T	3 T
Yes	Yes
Single	Single
Yes	Yes
Bike	Loop
Straight split	Straight split
26 mm	26 mm
7.60 kg	7.10 kg
287121102/ST2	287120102/ST2

# Petrol lawn trimmers



	GT 730 A	GT 330 A
Level	<b>Experience</b>	<b>Essential</b>
Series	<b>7</b>	<b>3</b>
<b>POWER</b>		
Power source	Petrol 2-stroke	Petrol 2-stroke
Power	1 kW	0.7 kW
Displacement	25.4 cc	25.4 cc
Engine rotation speed	6000 rpm	8800 rpm
Primer	Yes	Yes
Choke	Manual	Manual
Fuel tank capacity	0.45 L	0.65 L
<b>TRIMMING</b>		
Cutting width	38 cm	38 cm
Nylon head type	Bump & Work dual line	Tap & Go dual line
Nylon line length	4 m	4 m
Blade type	-	-
<b>COMFORT</b>		
Vibe Control System (VCS)	No	Yes
Harness	Single	No
Soft grip handle	Yes	Yes
Handle type	Loop	Loop
Shaft type	Curved Split	Curved Split
Shaft tube diameter	24 mm	26 mm
Product weight	5.20 kg	6.50 kg
Art. N.	283210108/ST1	287110102/ST2

# Corded brushcutters and lawn trimmers



	BC 110c A	GT 110c A	GT 106c	GT 104c
Level	<b>Essential</b>	<b>Essential</b>	<b>Essential</b>	<b>Essential</b>
Series	<b>1</b>	<b>1</b>	<b>1</b>	<b>1</b>
<b>POWER</b>				
Power source	Electric	Electric	Electric	Electric
Power	1 kW	1 kW	0.6 kW	0.35 kW
Motor type	With brushes	With brushes	With brushes	With brushes
<b>TRIMMING</b>				
Cutting width	37 cm	37 cm	30 cm	24 cm
Cutting angle	Fixed	Fixed	Adjustable	Fixed
Nylon head type	Tap & Go dual line	Tap & Go dual line	Tap & Go dual line	Tap & Go dual line
Nylon line length	8 m	5.4 m	3 m	3 m
Blade type	3 T	-	-	-
<b>COMFORT</b>				
Vibe Control System (VCS)	No	No	No	No
Harness	Single	Single	No	No
Soft grip handle	Yes	Yes	No	No
Handle type	Loop	Loop	Loop	Loop
Shaft type	Straight split	Curved Split	Telescopic	Full plastic
Shaft tube diameter	25 mm	25 mm	28 mm	-
Product weight	5.69 kg	4.76 kg	2.80 kg	2 kg
Art. N.	291851102/ST1	291850102/ST1	252060002/ST1	252035002/ST1

## CUTTING AND TRIMMING

# Battery pole trimmers and hedge trimmers



	PH 900e	HT 900e	PH 700e	HT 700e
Level	Expert	Expert	Experience	Experience
Series	9	9	7	7
POWER				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery kit	Not included	Not included	Not included	Not included
Voltage	48 V	48 V	48 V	48 V
Battery capacity	7.5 Ah	7.5 Ah	2 Ah	2 Ah
Suggested battery capacity	2 x 7.5 Ah	2 x 7.5 Ah	2 Ah	2 Ah
Lithium battery nominal energy	324 Wh	324 Wh	172.8 Wh	172.8 Wh
Working time (+/- 20%)	200 min	180 min	40 min	40 min
Motor type	Brushless	Brushless	With brushes	With brushes
TRIMMING				
Cutting length	50 cm	60 cm	48 cm	56 cm
Blade length	52 cm	65 cm	50 cm	63 cm
Blade type	Dual action - Laser cut	Dual action - Laser cut	Dual action - Laser cut	Dual action - Laser cut
Blade teeth speed	3300 spm	3300 spm	3000 spm	3000 spm
Teeth distance	34 mm	40 mm	34 mm	34 mm
Cutting capacity (diameter)	27 mm	33 mm	26 mm	26 mm
COMFORT				
Vibe Control System (VCS)	Yes	Yes	Yes	Yes
Handle type	Rear handle	Turnable 180° - 3 positions	Fix	Turnable 180° - 5 positions
Soft grip handle	Yes	Yes	Yes	Yes
TOOLS KIT				
Battery charger	Single fast	Single fast	Single standard	Single fast
Battery charger output current	1.5 A	1.5 A	1.5 A	2 A
Product weight	5.18 kg	4.60 kg	5 kg	4.62 kg
Art. N.	279710038/ST2	279350008/ST2	277710038/ST2	277300008/ST2



HT 500e	HT 500e Kit	HT 100 e Kit
<b>Experience</b>	<b>Experience</b>	<b>Essential</b>
<b>5</b>	<b>5</b>	<b>1</b>
Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Not included	Included	Included
48 V	48 V	20 V
2 Ah	2 Ah	2 Ah
2 Ah	2 Ah	2 Ah
86.4 Wh	86.4 Wh	36 Wh
50 min	50 min	40 min
With brushes	With brushes	With brushes
51 cm	51 cm	50 cm
58 cm	58 cm	55 cm
Dual action - Laser cut	Dual action - Laser cut	Dual action
3500 spm	3500 spm	2300 spm
27 mm	27 mm	25 mm
18 mm	18 mm	18 mm
No	No	No
Turnable 180° - 3 positions	Turnable 180° - 3 positions	Turnable 180° - 3 positions
Yes	Yes	No
Single standard	Single standard	Single standard
1.5 A	1.5 A	2 A
3.70 kg	4.58 kg	2.62 kg
278300008/ST3	278302108/ST3	271302108/ST2



# Petrol hedge trimmers



	HT 725	HT 525
Level	Experience	Experience
Series	7	5
POWER		
Power source	Petrol 2-stroke	Petrol 2-stroke
Power	0.65 kW	0.65 kW
Displacement	22.5 cc	22.5 cc
Engine rotation speed	10500 rpm	10500 rpm
Primer	Yes	Yes
Choke	Automatic	Automatic
Fuel tank capacity	0.26 L	0.26 L
TRIMMING		
Cutting length	56 cm	46 cm
Blade length	70 cm	60 cm
Blade type	Dual action - Laser cut	Dual action
Blade teeth speed	3000 spm	3000 spm
Teeth distance	35 mm	35 mm
Cutting capacity (diameter)	27 mm	27 mm
COMFORT		
Vibe Control System (VCS)	Yes	Yes
Handle type	Turnable 180° - 3 positions	Turnable 180° - 3 positions
Soft grip handle	Yes	Yes
Product weight	5.70 kg	5.60 kg
Art. N.	252422008/ST2	252421008/ST2

# Corded hedge trimmers



	HT 106c	HT 105c
Level	<b>Essential</b>	<b>Essential</b>
Series	<b>1</b>	<b>1</b>
<b>POWER</b>		
Power source	Electric	Electric
Power	0.6 kW	0.5 kW
Motor type	With brushes	With brushes
<b>TRIMMING</b>		
Cutting length	55 cm	45 cm
Blade length	60 cm	50 cm
Blade type	Dual action - Laser cut	Dual action
Blade teeth speed	1700 spm	1700 spm
Teeth distance	26 mm	22 mm
Cutting capacity (diameter)	20 mm	16 mm
<b>COMFORT</b>		
Vibe Control System (VCS)	No	No
Handle type	Turnable 180° - 5 positions	Turnable 180° - 5 positions
Soft grip handle	No	No
Product weight	3.25 kg	3.05 kg
Art. N.	256060002/ST1	256050002/ST1

# Battery multi-tool



	MT 500e	MT 500e Kit	MT 100e Kit
Level	Experience	Experience	Essential
Series	5	5	1
POWER			
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Power (hedger function)	0.35 kW	0.35 kW	0.15 kW
Power (pruner function)	0.35 kW	0.35 kW	0.28 kW
Battery kit	Not included	Included	Included
Voltage	48 V	48 V	20 V
Lithium battery nominal energy	86.4 Wh	86.4 Wh	72 Wh
Battery capacity	2 Ah	2 Ah	4 Ah
Suggested battery capacity	2 Ah	2 Ah	4 Ah
Hedger working time (+/- 20%)	40 min	40 min	70 min
Pruner working time (+/- 20%)	15 min	15 min	20 min
Motor type	With brushes	With brushes	With brushes
CUTTING			
Cutting length	44 cm	44 cm	41.5 cm
Blade length	46 cm	46 cm	45.5 cm
Teeth distance	28 mm	28 mm	18 mm
Chain type	3/8" .050" (91PX040E)	3/8" .050" (91PX040E)	3/8" .050" (91PJ033X)
Bar length	25 cm	25 cm	20 cm
Chain speed	5 m/s	5 m/s	5 m/s
Chain oil pump	Automatic	Automatic	
COMFORT			
Vibe Control System (VCS)	No	No	No
Harness	Single	Single	Yes
Soft grip handle	Yes	Yes	
Handle type	Loop	Loop	Rear handle
Shaft extension	65 cm	65 cm	55 cm
Product weight (hedger version)	6.10 kg	6.98 kg	3.10 kg
Product weight (pruner version)	5.60 kg	6.48 kg	3.20 kg
Art. N.	278720008/ST3	278722108/ST3	271724108/ST2

# Petrol multi-tool



	MT 330 – 5 in 1	Brushcutter	Hedge trimmer	Pruner
Level	Experience			
POWER				
Power source	Petrol 2-stroke	-	-	-
Power	0.7 kW	-	-	-
Displacement	25.4 cc	-	-	-
Engine rotation speed	1100 rpm	-	-	-
Starter	Easy start recoil	-	-	-
Primer	Yes	-	-	-
Choke	Manual	-	-	-
Fuel tank capacity	0.65 L	-	-	-
CUTTING				
Cutting width	-	43 cm	-	-
Nylon head type	-	Tap & Go dual line	-	-
Blade type (brushcutter)	-	3 T	-	-
Cutting length	-	-	40 cm	-
Blade length	-	-	43 cm	-
Teeth distance	-	-	25 mm	-
Bar length	-	-	-	25 cm
Chain type	-	-	-	3/8" .050" (91PJ-40X)
Chain speed	-	-	-	5.20 m/s
Chain oil pump	-	-	-	Automatic
COMFORT				
Vibe Control System (VCS)	Yes	-	-	-
Harness	Single	-	-	-
Soft grip handle	Yes	-	-	-
Handle type	Loop	-	-	-
Shaft extension	70 cm	-	-	-
TOOLS KIT				
Included tools kit	Spark plug key, screwdriver			
Product weight	7.10 kg	8.20 kg	9.20 kg	8.90 kg
Art. N.	287130152/ST2			

# Battery multi-mate



	SGM 102 AE	SGM 72 AE
Level	Essential	Essential
POWER		
Battery capacity	2.5 Ah	2.5 Ah
Power source	Lithium-ion battery	Lithium-ion battery
Battery kit	Included	Included
Motor type	With brushes	With brushes
Voltage	10.8 V	7.2 V
Working time (+/- 20%)	110 min	75 min
Hedger working time (+/- 20%)	160 min	110 min
Shrub shear cutting length	180 mm	180 mm
COMFORT		
Handle type	Turnable 180° - 3 positions	Fix
Product weight	0.83 kg	0.75 kg
Art. N.	253010241/ST1	253007231/ST1

## CUTTING AND TRIMMING

# Battery pole saws, pruner and chainsaw



	PS 900e	PS 700e	PR 700e	CS 700e
Level	<b>Expert</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
Series	<b>9</b>	<b>7</b>	<b>7</b>	<b>7</b>
<b>POWER</b>				
Power source	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery	Lithium-ion battery
Battery kit	Not included	Not included	Not included	Not included
Voltage	48 V	48 V	48 V	48 V
Lithium battery nominal energy	360 Wh	172.8 Wh	172.8 Wh	192 Wh
Battery capacity	7.5 Ah	4 Ah	4 Ah	4 Ah
Suggested battery capacity	2 x 7.5 Ah	4 Ah	4 Ah	4 Ah
Working time (+/- 20%)	22 min	30 min	12 min	16 min
Motor type	Brushless	With brushes	Brushless	Brushless
Overload protection	Yes	Yes	Yes	Yes
<b>CUTTING</b>				
Bar length	10" / 25 cm	10" / 25 cm	12" / 30 cm	14" / 35 cm
Bar type	Sprocket nose	Sprocket nose	Sprocket nose	Sprocket nose
Speed selector	Yes	No	No	Yes
Chain brake	No	No	Manual	Manual
Chain speed	12-16 m/s	5 m/s	20 m/s	16-20 m/s
Chain tensioning system	Side screw tensioning	Side screw tensioning	Side screw tensioning	Side screw tensioning
Chain type	3/8" .050" (91PX-40X)	3/8" .050" (91PX040E)	3/8" .050" (91PX045E)	3/8" .050" (91PX-52X)
Chain oil pump	Automatic	Automatic	Automatic	Automatic
Chain oil tank capacity	0.10 L	0.15 L	0.18 L	0.18 L
<b>COMFORT</b>				
Handle type	Fix	Rear handle	Top handle	Rear handle
Soft grip handle	Yes	Yes	Yes	Yes
<b>TOOLS KIT</b>				
Battery charger	Dual standard	Single standard	Single standard	Single standard
Battery charger output current	3 A	1.5 A	1.5 A	1.5 A
Product weight	4.20 kg	5.60 kg	3.45 kg	3.45 kg
Art. N.	279710048/ST2	277710048/ST2	278420008/ST3	277430008/ST1



# Petrol pruners and chainsaws



	PR 730 C (10")	PR 730 (10")	CS 755 (20")	CS 755 (18")
Level	Experience	Experience	Experience	Experience
Series	7	7	7	7
POWER				
Power source	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
Power	0.70 kW	0.70 kW	2.30 kW	2.30 kW
Displacement	26.90 cc	26.90 cc	52 cc	52 cc
Primer	Yes	Yes	Yes	Yes
Choke	Manual with automatic return	Manual with automatic return	Manual with automatic return	Manual with automatic return
Fuel tank capacity	0.22 L	0.22 L	0.47 L	0.47 L
Included tools kit	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key
CUTTING				
Bar length	25 cm	25 cm	50 cm	45 cm
Bar length (inches)	10 "	10 "	20 "	18 "
Bar type	Carving	Sprocket nose	Sprocket nose	Sprocket nose
Chain brake	Manual and inertial	Manual and inertial	Manual and inertial	Manual and inertial
Chain speed	20.32 m/s	22.86 m/s	23.10 m/s	23.10 m/s
Chain tensioning system	Side screw tensioning	Side screw tensioning	Side screw tensioning	Side screw tensioning
Chain type	1/4" .050" (E1-25AP-60T)	3/8" .050" (91PX-40X)	.325" .058" (21BPX-78X)	.325" .058" (21BPX-72X)
Chain oil pump	Automatic	Automatic	Automatic adjustable	Automatic adjustable
Chain oil tank capacity	0.17 L	0.17 L	0.26 L	0.26 L
COMFORT				
Handle type	Top handle	Top handle	Rear handle	Rear handle
Soft grip handle	Yes	Yes	Yes	Yes
Product weight	4.88 kg	4.87 kg	8.12 kg	8.01 kg
Art. N.	240271012/ST2	240271002/ST2	240522002/ST1	240521802/ST1



CS 755 (15")	CS 750 (18")	CS 750 (15")	CS 545 (16")
<b>Experience</b>	<b>Experience</b>	<b>Experience</b>	<b>Experience</b>
<b>7</b>	<b>7</b>	<b>7</b>	<b>5</b>
Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
2.30 kW	2 kW	2 kW	1.90 kW
52 cc	46.50 cc	46.50 cc	42.40 cc
Yes	Yes	Yes	Yes
Manual with automatic return	Manual with automatic return	Manual with automatic return	Manual with automatic return
0.47 L	0.47 L	0.47 L	0.51 L
Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key
38 cm	45 cm	38 cm	40 cm
15 "	18 "	15 "	16 "
Sprocket nose	Sprocket nose	Sprocket nose	Sprocket nose
Manual and inertial	Manual and inertial	Manual and inertial	Manual and inertial
23.10 m/s	23.10 m/s	23.10 m/s	23.10 m/s
Side screw tensioning	Side screw tensioning	Side screw tensioning	Side screw tensioning
.325" .058" (21BPX064X)	.325" .058" (21BPX-72X)	.325" .058" (21BPX064X)	.325" .050" (95TXL-66X)
Automatic adjustable	Automatic adjustable	Automatic adjustable	Automatic adjustable
0.26 L	0.26 L	0.26 L	0.26 L
Rear handle	Rear handle	Rear handle	Rear handle
Yes	Yes	Yes	Yes
8.30 kg	8.02 kg	8.21 kg	7.62 kg
240521502/ST1	240461802/ST1	240461502/ST1	240421602/ST1

# Petrol chainsaws



	CS 545 (15")	CS 540 (16")	CS 540 (14")	CS 330 (12")
Level	Experience	Experience	Experience	Essential
Series	5	5	5	3
POWER				
Power source	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke	Petrol 2-stroke
Power	1.90 kW	1.60 kW	1.60 kW	0.85 kW
Displacement	42.40 cc	38.50 cc	38.50 cc	30.10 cc
Primer	Yes	Yes	Yes	Yes
Choke	Manual with automatic return	Manual with automatic return	Manual with automatic return	Manual with automatic return
Fuel tank capacity	0.51 L	0.51 L	0.51 L	0.22 L
Included tools kit	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key	Screwdriver, chain round file, spark plug key
CUTTING				
Bar length	38 cm	40 cm	35 cm	30 cm
Bar length (inches)	15 "	16 "	14 "	12 "
Bar type	Sprocket nose	Sprocket nose	Sprocket nose	Sprocket nose
Chain brake	Manual and inertial	Manual and inertial	Manual and inertial	Manual and inertial
Chain speed	23.10 m/s	22.80 m/s	22.80 m/s	22.86 m/s
Chain tensioning system	Side screw tensioning	Side screw tensioning	Side screw tensioning	Side screw tensioning
Chain type	.325" .050" (95TXL064X)	3/8" .050" (91PX057X)	3/8" .050" (91PX-53X)	3/8" .050" (91PX-45X)
Chain oil pump	Automatic adjustable	Automatic adjustable	Automatic adjustable	Automatic
Chain oil tank capacity	0.26 L	0.26 L	0.26 L	0.17 L
COMFORT				
Handle type	Rear handle	Rear handle	Rear handle	Rear handle
Soft grip handle	Yes	Yes	Yes	Yes
Product weight	7.49 kg	7.31 kg	7.30 kg	4.90 kg
Art. N.	240421502/ST1	240381602/ST1	240381402/ST1	240311202/ST2

# Corded chainsaw



	CS 118c (14")	CS 122c (16")
Level	<b>Essential</b>	<b>Essential</b>
Series	<b>1</b>	<b>1</b>
<b>POWER</b>		
Power source	Electric	Electric
Power	1.8 kW	2.2 kW
Motor type	With brushes	With brushes
<b>CUTTING</b>		
Bar length	35 cm	40 cm
Bar length (inches)	14 "	16 "
Bar type	Sprocket nose	Sprocket nose
Chain brake	Manual and inertial	Manual and inertial
Chain speed	10 m/s	11 m/s
Chain tensioning system	Side screw tensioning	Quick side tensioning
Chain type	3/8" .050" (91PX052E)	3/8" .050" (91PX056E)
Chain oil pump	Automatic	Automatic
Chain oil tank capacity	0.18 L	0.25 L
<b>COMFORT</b>		
Handle type	Rear handle	Rear handle
Soft grip handle	Yes	Yes
<b>TOOLS KIT</b>		
Included tools kit	Screwdriver	Screwdriver
Product weight	5.40 kg	5.90 kg
Art. N.	292614008/ST2	292616168/ST2

# Chipper and shredders

**BIO SILENT 2500****BIO MASTER 2200**

Level	<b>Essential</b>	<b>Essential</b>
<b>POWER</b>		
Power source	Electric	Electric
Power	2.5 kW	2.2 kW
Motor type	Brushless	With brushes
<b>CUTTING</b>		
Cutting method	Rotating roller with 8 teeth	Double reversible knives
Maximum branch diameter	40 mm	40 mm
Reverse function	Yes	No
Adjustable working width	Yes	No
<b>COMFORT</b>		
Collector capacity	60 L	50 L
Collector type	Plastic	Textile
Guaranteed sound power level (LwA)	97 dB(A)	102 dB(A)
<b>TOOLS KIT</b>		
Included tools kit	Feeder	Feeder
Product weight	27.43 kg	11.31 kg
Art. N.	290001252/14	290000222/ST1

# Petrol scarifiers

**SVP 40 G**

Level	Experience
<b>POWER</b>	
Power source	Petrol 4-stroke
Power	4 kW
Displacement	182 cc
Starter	Recoil
Fuel tank capacity	3600 rpm
Engine Oil tank capacity	3 L
Engine rotation speed	0.60 L
<b>CUTTING</b>	
Working method	32 floating knives
Working width	40 cm
Working depth	1.50 cm
Number of blades	32
<b>COMFORT</b>	
Collector capacity	50 L
Wheels size	180 mm
Product weight	44 kg
Art. N.	211400248/ST1

# Corded scarifiers

**SV 415 E****SV 213 E**

Level	Essential	Essential
<b>POWER</b>		
Power source	Electric	Electric
Power	1.5 kW	1.3 kW
Motor type	With brushes	With brushes
<b>CUTTING</b>		
Working method	20 blades or 44 springs	16 blades or 36 springs
Working width	38 cm	32 cm
Working depth	1.30 cm	0.60 cm
Number of blades	20	16
Number of springs	44	36
Double function	Yes	Yes
<b>COMFORT</b>		
Collector capacity	50 L	40 L
Wheels size	160 mm	200 mm
Product weight	14.50 kg	10.20 kg
Art. N.	290002152/14	290002132/14

# Petrol tillers



	SRC 775 RB	SRC 685 RG	SRC 775 RG	SRC 550 RG
Level	Expert	Experience	Experience	Experience
POWER				
Power source	Petrol 4-stroke	Petrol 4-stroke	Petrol 4-stroke	Petrol 4-stroke
Power	3.9 kW	3.5 kW	3.1 kW	1.66 kW
Displacement	208 cc	182 cc	182 cc	125 cc
Engine model	B&S 950 CR Series	TM 60	TM 60	ST 120 OHV
Engine Brand	Briggs & Stratton	STIGA	STIGA	STIGA
Fuel tank capacity	3.1 L	3 L	3 L	0.80 L
Gear case oil capacity	0.50 L	0.50 L	0.50 L	0.20 L
Air filter type	Paper	Oil bath	Sponge	Sponge
CUTTING				
Transmission type	Chain and gear in oil bath + belt	Chain and gear in oil bath + belt	Chain and gear in oil bath + belt	Worm and gear in oil bath + belt
Number of gears	1 forward + 1 reverse	2 forward + 1 reverse	1 forward + 1 reverse	1 forward + 1 reverse
Working width	75 cm	85 cm	75 cm	50 cm
Rotors diameter	320 mm	245 mm	320 mm	260 mm
Rotors number	6	6	6	4
Tree saver discs	Yes	Yes	Yes	Yes
COMFORT				
Wheel type	Plastic	Plastic + Rubber	Plastic	Plastic
Transport wheels	1 front wheel	1 front wheel	1 front wheel	2 rear wheels
Adjustable handlebar	Vertical and horizontal	Yes	Vertical and horizontal	Vertical and horizontal
Soft grip handle	No	Yes	No	No
Product weight	53 kg	62.50 kg	53 kg	42 kg
Art. N.	212751122/14	213851142/ST1	212751142/14	212501042/ST1



## SOIL AND GROUND CARE

# Petrol scythe



### SRC 36 V

#### Essential

Petrol 4-stroke

1.9 kW

123 cc

ST 120 OHV Autochoke

STIGA

0.75 L

0.25 L

Sponge

Worm and gear in oil bath + belt

1 forward

36 cm

245 mm

4

No

Plastic + Rubber

1 front wheel

Yes

Yes

29 kg

211360042/ST1



### Silex

### 103 B

### 95 H

### 87 G

Level

Experience

Experience

Experience

#### POWER

Power source

Petrol 4-stroke

Petrol 4-stroke

Petrol 4-stroke

Power

4.8 kW

3.3 kW

2.2 kW

Displacement

208 cc

160 cc

123 cc

Engine Brand

Briggs & Stratton

Honda

STIGA

Engine model

B&S 950 CR Series

GCV 160

ST 120 OHV

Fuel tank capacity

3.8 L

0.9 L

0.9 L

Air filter type

Compressed fiber

Compressed fiber

Sponge

#### CUTTING

Transmission type

Chain and gear in oil bath + belt

Worm and gear in oil bath + belt

Worm and gear in oil bath + belt

Number of gears

2 forward + 1 reverse

1 forward + 1 reverse

1 forward

#### COMFORT

Wheel type

Pneumatic

Pneumatic

Pneumatic

Transport wheels

15x5.00-6

13x5.00-6

13x5.00-6

Adjustable handlebar

Yes

Yes

Yes

Soft grip handle

No

No

Yes

Product weight

70 kg

47 kg

46 kg

Art. N.

210310022/10

219510032/10

210870042/ST2

# Batteries and chargers

## 48V batteries



	E 475	E 450	E 440	E 420
Voltage	48 V	48 V	48 V	48 V
Capacity	7.5 Ah	5 Ah	4 Ah	2 Ah
Charging time fast / std	330 min / 180 min	220 min / 120 min	180 min / 110 min	90 min / 50 min
Weight	2.12 kg	1.44 kg	1.36 kg	0.88 kg
Art. N.	277017008/ST1	277015008/ST1	277014008/ST1	277012008/ST1

## 48V chargers



	EC 415 D	EC 430 F	EC 415 S
Voltage	48 V	48 V	48 V
Plug type	Eu plug	Eu plug	Eu plug
Type	Dual standard	Fast	Single standard
Output current	1.5 Ah	3 Ah	1.5 Ah
Art. N.	277020208/ST1	277030008/ST1	277020008/ST1

## Battery harness

### BH 900e

Voltage	48 V
Capacity	Max. 2 batteries
Weight	4.60 kg
Art. N.	279050008/ST2



## Battery simulator



### E 400 S

Weight	0.35 kg
Art. N.	27010008/ST1

## Battery belt

### BB 700e

Tools Kit	Holder, belt, cable
Weight	1.60 kg
Art. N.	277040008/ST1



## 20V chargers



	C 215 D	C 215 S
Voltage	1.5 Ah	1.5 Ah
Plug type	Eu plug	Eu plug
Type	Dual standard	Single standard
Output current	2 A	2 A
Art. N.	271020100/21	271020000/21

## 20V batteries



	E 24	E 22
Voltage	20V	20V
Battery type	Lithium-ions	Lithium-ions
Capacity	4 Ah	2 Ah
Charging time	140 min	70 min
Weight	0.64 kg	0.39 kg
Art. N.	271014008/ST1	271012008/ST1

# Robot mowers



Code	Pos.	Description	Fits for	Specification
1127-0012-01	-	Installation KIT Small	STIG	150 m - Ø 2.7 mm cable + 200 pegs + 5 fast connectors + 5 docking station connectors
1127-0013-01	-	Installation KIT Medium	STIG	300 m - Ø 2.7 mm cable + 400 pegs + 5 fast connectors + 5 docking station connectors
1127-0000-01	-	Cable reel 150 mt	STIG	Ø 2.7 mm - L 150 m
1127-0001-01	-	Cable reel 300 mt	STIG	Ø 2.7 mm - L 300 m
1127-0002-01	-	Cable reel 500 mt	STIG	Ø 3.4 mm - L 500 m
1127-0004-01	-	Fast connectors	STIG	5 pcs
1127-0005-01	-	Docking station connectors	STIG	5 pcs
1127-0006-01	-	Pegs (100 pcs)	STIG	100 pcs
1127-0008-01	-	Docking station pegs	STIG	8 pcs
1127-0009-01	-	Razors	STIG	Blister with 12 blades
1127-0010-01	-	Cable extension for charger	STIG	5 mt wire extension for charger
1127-0011-01	-	Docking station cover	STIG	N.A.

# Lawn mowers



1



2

## Engine kits

Code	Pos.	Type	Fits for
1111-9285-01	1	Engine service kit	For Briggs & Stratton 300E-450E-500E series
1111-9286-01	1	Engine service kit	For Briggs & Stratton 550E-575E-625E Series
1111-9287-01	1	Engine service kit	For Briggs & Stratton DOV 700E-750EX-775iS Series
1111-9288-01	1	Engine service kit	For Briggs & Stratton 650Exi-675 Exi Series - 675iS Series
1111-9289-01	1	Engine service kit	For ST WBE170, ST WBE170 LS
1111-9301-01	1	Engine service kit	For WBE120 - 140
1134-9188-01	2	Kit oil and fuel extractor	Suitable for extraction of oil and fuel from all 4 stroke engines



1 - 2

### Packaging

Dimensions: 28 x 21 x 9 cm

Gross weight small: 0.565 kg approx.

Gross weight large: 0.680 kg approx.



3

### Packaging

Dimensions: 11.5 x 3.5 x 11 cm

Gross weight: 0.150 kg approx.

## Maintenance

Code	Pos.	Description	Measures
1111-9225-01	1	Small protective cover for walk-behind	145 x 50 x 110 cm
1111-9226-01	2	Large protective cover for walk-behind	180 x 50 x 110 cm
1111-9227-01	3	Scrapper	

# Front mowers

Products	Code	Pos.	Park 300M	Park 300	Park 500	Park 500 W
Cargo rails for Park Pro <sup>(1)</sup>	2A0000060/S16	1				
Carrier Case	2A4052000/S16	2				
Combi cart plastic	13-0952-11	3	X	X	X	X
Dust cover for sweeper 85 cm	13-3916-61	4			X	X
Dust cover for sweeper 95 cm	13-1936-62	4			X	X
Edge cutter 2+4WD	13-3911-61	5			X	X
Fertiliser spreader	13-0955-11	6	X	X	X	X
Flail mower axle <sup>(1)</sup>	13-1985-11	7				
Flail mower EL complete, Park 2+4 WD	13-3902-11	8				
Flail mower, complete, Park 2+4 WD	13-0976-11	9				
Frame weights 2x13,5 kg <sup>(1)</sup>	13-0921-62	10				
Frame weights 2x17 kg	13-0939-61	11			X	X
Grass & leaf collector 42"	13-3926-11	12	X	X	X	X
Grass & leaf collector 42" compact	2A6107010/S17	13	X	X	X	X
Lawn rake axle <sup>(1)</sup>	13-1986-11	14				
Lawn rake EL complete, Park 2+4 WD	13-3901-11	15				
Lawn rake, complete, Park 2+4WD	13-0975-11	16				
Mulching Kit (Including blades)	2A0130060/ST1	17				
Poly Roller	299900260/0	18	X	X	X	X
Pro cart galvanized	13-3906-11	19	X	X	X	X
Protective cover Stiga	2A0000000/S16	20	X	X	X	X
RAC Quick connection <sup>(1) (2)</sup>	13-0994-61	21				
RAC Quick connection 2WD Park <sup>(1) (2)</sup>	13-0992-62	22				
RAC Quick connection 4WD Park <sup>(1) (2)</sup>	13-0993-61	22				
Rake tool 100 cm Park (in combination with tool lift)	13-3913-11	23				
Rake tool 130 cm Park (in combination with tool lift)	13-3914-11	24				
Rear tool lift, Electric, Park	13-3919-11	25				
Rear tool lift, manual, Park	13-3909-11	26				
Rubber scraper bar 107 cm <sup>(1)</sup>	13-3904-61	27				
Rubber scraper bar 120 cm	13-1958-62	27			X	X
Rubber scraper Hydraulic blade	13-3934-61	27				
Rubber scraper Hydraulic X Blade	13-3933-61	28				
Sand spreader Park	13-1975-14	29				
Side brush accessory	13-3915-11	30				
Snow blade 107 cm universal <sup>(1)</sup>	13-3922-61	31				
Snow blade 120 cm Park	13-3917-61	32			X	X
Snow Blade for Park 120 -220	2A3107020/S16	33	X	X		
Snow Blade Park Hydraulic	13-3932-11	34				
Snow chains 16"x6 <sup>(1)</sup>	13-0940-61	35				
Snow Chains 16"x7,5	13-0936-61	36			X	X
Snow Chains 160/50-8	13-3927-61	36	X	X		
Snow Chains 17"x8	13-0937-61	36				
Snow thrower 2-stage Hydraulic	13-3930-11	37				
Snow thrower 2-stage Park Pro	13-0922-12	38				
Snow thrower Park 2+4WD	13-0974-11	39			X	X
Snow tyres spikes	299900450/0	40			X	X
Spring hoe	13-0978-61	41			X	X
Sweeper for Park 120 - 220	2A1100040/S16	42	X	X		
Sweeper Park 2+4 WD	13-0977-11	43			X	X
Sweeper Park hydraulic	13-3929-11	44				
Sweeper Villa e Park 2+4WD	13-3918-61	45			X	X
Sweeper with collector	13-3910-11	46				
Trailer hitch	2A0000060/ST1	47				
Winter wheels Park, pair 16"	2A9000050/S16	48			X	X
X blade Park Hydraulic	13-3931-11	49				
ZTR 52" Mulching Kit (Including blades)	2A0130060/S17	50				

(1) Compatible with the old range

(2) Park models already equipped with RAC

ACCESSORIES

	Park 500 WX	Park Special	Park 700 W	Park 700 WX	Park 900 WX	Park Pro 900 WX	Park Pro 900 AWX	ZT 5132 T	ZT 7132 T
						X	X		
	X	X	X	X	X	X	X		
	X	X	X	X	X				
	X	X	X	X	X	X	X		
	X	X	X	X	X	X	X		
	X	X	X	X	X	X	X		
			X	X	X	X	X		
			X	X	X	X	X		
	X	X	X	X	X				
	X	X	X	X	X	X	X		
	X	X	X	X	X	X	X		
			X	X	X	X	X		
			X	X	X	X	X		
									X
	X	X	X	X	X	X	X		
	X	X	X	X	X	X	X		
	X	X	X	X	X	X	X		
			X	X	X	X	X		
			X	X	X	X	X		
						X	X		
			X	X	X	X	X		
	X	X	X	X	X	X	X		
							X		
							X		
						X	X		
						X	X		
	X	X	X	X	X	X	X		
							X		
	X	X	X	X	X				
	X	X	X	X	X				
	X	X	X	X	X				
	X	X	X	X	X	X	X		
									X
	X	X	X	X	X				
			X	X	X	X	X		
	X	X	X	X	X	X	X		
							X		
									X
	X	X	X	X	X	X	X		
							X		
								X	



## ACCESSORIES



1. Cargo rails



2. Carrier Case



3. Combi cart




4. Dust cover



5. Edge cutter



6. Fertiliser spreader



7. Flail mower axle



8. Flail mower complete



9. Flail mower complete



10. Frame weights




11. Frame weights



12. Grass & leaf collector



13. Grass & leaf collector



14. Lawn rake axle



15. Lawn rake complete



16. Lawn rake complete



17. Mulching Kit



18. Poly Roller



19. Pro cart galvanized



20. Protective cover Stiga



21. RAC Quick connection



22. RAC Quick connection



23. Rake tool



24. Rake tool



25. Rear tool lift electric

## ACCESSORIES



26. Rear tool lift manual



27. Rubber scraper bar / blade



28. Rubber scraper blade



29. Sand spreader



30. Side brush



31. Snow blade



32. Snow blade



33. Snow blade



34. Snow blade



35. Snow chains



36. Snow chains



37. Snow thrower



38. Snow thrower



39. Snow thrower



40. Snow tyres spikes



41. Spring hoe



42. Sweeper



43. Sweeper



44. Sweeper



45. Sweeper



46. Sweeper



47. Trailer hitch



48. Winter wheels



49. X blade



50. Mulching Kit

# Zero turn mowers



1. Mulching kit



2. Trailer hitch



3. Trailer hitch



4. Mulching kit



5. Mulching kit

Product	Pos.	Code	ZT 5132 T	ZT 7132 T
Mulching Kit (Including blades)	1	2A0130060/ST1		X
Trailer hitch	2	2A0000060/S17		
Trailer hitch	3	2A0000060/ST1		X
ZTR 52" Mulching Kit (Including blades)	5	2A0130060/S17	X	



1



2

## Blades

Code	Pos.	Description	Fits for	Length	Type	Note
1134-9211-02	1	Blade	ZT 5132 T	457	Standard	Package of 3
1134-9238-01	2	Blade	ZT 7132 T	457	Mulching	Package of 3

# Lawn tractors



Code	Pos	Description	Fits for	Length	Type	Width	Q.ty
1134-9232-01	1	Blade	Tornado 6118 HW, 7118 HWS, Pro 9118 XWS	417 mm	mulching	118 cm	3
1134-9233-01	2	Blade	Tornado 6118 HW, 7118 HWS, Pro 9118 XWS	417 mm	winged	118 cm	3
1134-9220-01	2	Blade RH + Blade LH	SC 84, SC 84 B, ESTATE 2084, ESTATE 2084 H, ESTATE 3084 H, ESTATE 3098 H	418 mm	mulching winged	84 cm	1 + 1
1134-9224-01	2	Blade RH + Blade LH	Estate Collector, Senator, President, SC: 9013, 9214 (2011-), ESTATE 4092 H, ESTATE 5092 H	457 mm	winged	92 cm	1 + 1
1134-9226-01	2	Blade RH + Blade LH	Estate 3098 H, 3398 H, 3398 HW, Estate 3098 H	490 mm	winged	98 cm	1 + 1
1134-9234-01	2	Blade RH + Blade LH	Estate 3098 H, 3398 H, 3398 HW, Estate 3098 H	490 mm	mulching	98 cm	1 + 1
1134-9221-01	3	Blade RH + Blade LH	Estate Master, Master Hst, 2084, ESTATE 2084 H, ESTATE 3084 H	418 mm	mulching	84 cm	1 + 1
1134-9225-01	3	Blade	Estate Tornado, Tornado 14, HST 17, Pro HST 13; SD: 9813, 9812 (2011-), 9814 H (2011-), 98 B, 2098, 2098 H	486 mm	mulching	98 cm	1 + 1
1134-9223-01	3	Blade RH + Blade LH	Estate Collector, Senator, President, SC: 9013, 9214 (2011-), ESTATE 4092 H, ESTATE 5092 H	456 mm	mulching	92 cm	1 + 1
1134-9222-01	4	Blade RH + Blade LH	Estate Collector, President, Senator, Senator 14, HST 17, Pro HST 17 (2011), Senator HST, Senator HST Special, Senator H HST; SC: 9013, 9214, 92H, 92 B, 6092 HW, ESTATE 4092 H, ESTATE 5092 H	460 mm	mulching winged	92 cm	1 + 1
1134-9229-01	4	Blade RH + Blade LH	Estate Grand Royal 22, Grand Overland 24E/24 Four-wheel drive/Pro 25 Four-wheel drive E (2010), Grand Royal, Grand Overland Four-wheel drive/ PRO Four-wheel drive E, PRO 9122 HWS, ESTATE PRO 9122 XWSY, ESTATE 7122 HWS	617 mm	mulching winged	122 cm	1 + 1
1134-9227-01	5	Blade RH + Blade LH	Estate Royal, 19 (2010-), Pro 17 (2010-), Pro, Overland, Overland 22 Four-wheel drive (2010-), Royal special, Royal H, Overland Four-wheel drive, Estate: 5102 H, 5102 HW, 7102 HWSY; ST: 10214, 10216 H (2011-), 102, 6102 HW, PRO 9102 XWS	517 mm	mulching winged	102 cm	1 + 1
1134-9228-01	6	Blade RH + Blade LH	Estate Royal, Royal 19 (2010-), Pro 17 (2010-), Pro, Overland, Overland 22 Four-wheel drive (2010-); ST 10214, ESTATE 6102 HW, PRO 9102 XWS	518 mm	winged	102 cm	1 + 1
1134-9231-01	7	Blade	Estate Grand Tornado 17, HST 19, Pro HST 17 (2011-), Grand Tornado, Grand Tornado HST, Grand Tornado H HST; SD: 108 H, 10816, 5108 HW, Tornado 5108 HW, TORNADO 4108 H, 5108 H, 6108 HW, 7108 HWS, 3108 H, 3108 HW, 4108 H, 7108 HWSY	533 mm	mulching winged	108 cm	2
1134-9219-01	9	Blade	Garden: Combi, Combi HST 14, Combi HST, Combi H HST, Pro HST 13, Combi 3072	707 mm	mulching winged	72 cm	1
1134-9230-01	8	Blade RH + Blade LH	Estate Grand Royal 22, Grand Overland 24E/24 Four-wheel drive/Pro 25 Four-wheel drive E (2010-), ESTATE 7122 HWS	618 mm	winged	122 cm	1 + 1
1134-9218-01	8	Blade	SR: 66E, 66 EB, Garden: Compact E HST, Compact E HST B, Combi: 1066H, 1066HQ, Tornado 1066H	649 mm	mulching	66 cm	1

# Lawn tractors

Products	Code	Pos.	Swift (72 cm)	Coll. 3-5 series (84 cm)	Coll. 7 series (98 cm)	Side dis. 3-5 series (98 cm)	Side dis. 7 series (108 cm)	Combi 1 series (66 cm)	Combi 3 series (72 cm)
Rear deflector	299900311/0	N.A.	x						
	299900310/0	1		x	x				
	299900016/0	2							
Mulching kit (plug)	299900044/0	N.A.	x						
	2I0300001/21	N.A.							
	2I0330001/21	N.A.							
	2I0205000/19	3		x					
	2I0205001/19	4			x				
	299900341/0	5				x			
	299900346/0	6					x		
	299900135/0	7						x	
	299900036/0	8							x
	299900038/1	N.A.							
	299900055/0	9							
	299900046/0	10							
	299901055/0	11							
	299901056/0	12							
	299900037/0	13							x
Mulching kit (plug & blades)	299900370/1	14		x					
	299900374/0	15			x				
	299900070/1	N.A.							
	299900074/0	16							
	299900076/0	17							
	2I0330000/17	18							
	299901074/0	19							
	299901077/0	20							
PTO kit (multi connect system)	2I0300000/17	21							
	299900750/1	22							
Trailer hitch	2I1000100/17	23							
	299900395/0	24		x	x				
	299900006/0	25							
	2I0000000/17	26							
	299901006/0	27							
Combi cart	299900385/0	28				x	x		
	13-0952-11	29		x	x	x	x		
	Pro cart galvanized	30		x	x	x	x		
	Grass & leaves collector 42" compact	2A6107010/S17	31						
	Fertilizer spreader	13-0955-11	32	x	x	x	x		
	Sand spreader <sup>(1)</sup>	13-1975-14	33						
	Poly roller 23"	299900260/0	34						
	Poly roller 36"	2I0800100/18	34						
		2I0900100/17	35						
	Rear weight	299900150/0	36						
	Winter tyres 18"	299900430/0	37	x	x	x	x		
	Winter tyres 20"	2I1500000/18	37						
	Snow chain 18"	299900470/1	38	x	x	x			
	Snow chain 20"	299900480/1	38						
	Snow tyre spikes	299900450/0	39	x	x	x	x		
	Snow blade 107 cm	299903410/1	40	x	x	x	x		
	Snow blade 120 cm	299900400/0	40						
	Snow blade 120 cm (Multi Connect System)	299900400/1	40						
	Snow blade 125 cm (Multi Connect System)	2I1300100/17	40						
	Sweeper 105 cm (Multi Connect System) <sup>(2)</sup>	299900500/1	41						
	Sweeper 120 cm (Multi Connect System)	2I1200100/17	42						
	Green keeper 110 cm (Multi Connect System)	2I1900100/17	43						
	Flail mower 105 cm (Multi Connect System)	299900540/0	44						
	Lawn striping kit	2I2120000/18	45						
Stiga protective cover	1134-9177-01	46	x	x	x	x	x	x	x
Phone holder Stiga classic <sup>(3)</sup>	1134-9328-01	N.A.	x	x		x			
Phone holder Stiga comfort <sup>(3)</sup>	1134-9329-01	N.A.	x	x	x	x	x		
Stiga battery e 450 - 5.0 Ah	277015008/ST1	47	x						
Stiga battery e 475 - 7.5 Ah	277017008/ST1	48	x						
Battery charger (petrol tractors) <sup>(4)</sup>	182180190/0	N.A.							x

(1) Need to order the cable 182040074/0

(2) Front rubber for sweeper 299900505/1

(3) Availability & price to be defined

(4) Availability to be defined

## ACCESSORIES

[illegible]



## ACCESSORIES



26. Trailer hitch



27. Trailer hitch



28. Trailer hitch



29. Combi cart



30. Pro cart galvanized



31. Grass & leaves collector



32. Fertilizer spreader



33. Sand spreader



34. Poly roller



35. Rear weight



36. Rear weight



37. Winter tyres



38. Snow chain



39. Snow tyre spikes



40. Snow blade



41. Sweeper



42. Sweeper



43. Green keeper



44. Flail mower



45. Lawn striping kit



46. Stiga protective cover



42. Stiga battery E 450



43. Stiga battery E 475



